

cles, bridge/dam/hillside/building structure monitoring, drone aerial photography/logistics/artistic performance, handheld/wearable devices, precision agriculture, shared movement/tracking management, V2V/V2X, and more.

LOCOSYS

www.locosystech.com

Module for smart city infrastructure

ROHM has developed Wi-SUN FAN (field area network) module BP35C5 that is capable of connecting up to 1,000 devices (like traffic signals and streetlights) wirelessly in a mesh network to cover an entire city. This international



wireless communication standard module eliminates the communication costs associated with conventional low-power wide-area wireless standards. It ensures superior reliability through multi-hop networks that automatically switch destinations after signal verification. The BP35C5, an in-house ultra-small (15.0mm × 19.0mm) module, is expected to see widespread use in large-scale mesh networks for smart cities and smart grids. It can carry out secure communication without the need for complicated control.

ROHM Semiconductor

www.rohm.com

Analogue DC-DC converter

The new PKU4913D converter claims excellent electrical and thermal performance at affordable cost. Efficiency is typically 94.6% at Vin, 48V at full load. Aimed primarily at telecom applications, it has input voltage range of 36 to 75V, which meets the requirements



for normal input voltage range in -48 and -60V DC systems. It provides an output of up to 8.3A at 12V, thus delivering

100W, with output voltage trimming of up to 10%. Input to output isolation is 2,250V. PKU4913D is supplied in low-profile 1/16 brick format, measuring 33.02mm × 22.86mm × 11.30mm. The converter includes over-voltage, over-temperature, and short-circuit protection, which increase reliability and operational lifespan. It has a mean time between failures of 13.88 million hours.

Flex Power Modules

www.flexpowermodules.com

48V DC input power supply

This 48V DC-input power supply CSU2000ADC-3 is designed to provide high power in a small form factor for compute, storage, and networking applications. With 12V output at 2,000W, it is perhaps the industry's only 2kW carrier-




grade power supply providing scalability and power capacity flexibility while satisfying carrier requirements for input cabling. It features common redundant power supply form factor, making it simple for customers to design their systems. With applications in traditional AC data centres, DC telco central offices, and DC data centres, it reduces customers' development time, cost, and risk.

Advanced Energy

www.advancedenergy.com

Compact 1,200W power supply

The RACM1200-V baseplate-cooled fanless power supply comes as a compact, single output AC/DC converter. Just 228mm × 96.2mm × 40mm in size, it can deliver 1,000 watts continuously with the baseplate held to 80°C and 1,200 watts for up to ten seconds, or continuously with airflow. Input is universal 85-264V AC, dip-switch adjustable outputs available are nominal 24V



and 48V DC, with 36V DC expected soon, and efficiency is 95% peak. An isolated and 'always

on' 5V/1A auxiliary supply is provided along with an adjustable 5V to 12V/1A system fan output, with all outputs isolated from ground to 2kV AC for PoE applications. The power supply has safety certifications for industrial, ITE, and medical applications with 2 × MOPP isolation and low leakage current for BF applications. An integrated microprocessor implements comprehensive protection features and monitors output current, temperature, and other parameters to provide smart control and automatic

protection in case of improper use or overloading.

RECOM

www.recom-power.com

Automotive smart camera

Renesas EagleCAM module is an open front camera solution, featuring Renesas' R-Car V3H and R-Car V3M system-on-chip (SoC). The all-in-one scalable camera platform targets such requirements as automatic emergency braking, forward collision warning, lane



keeping assist, and traffic sign recognition. Developed together with LUPA-

Electronics, it introduces an open turnkey solution that delivers flexible, high-performance perception while shortening time to market and reducing the bill of materials costs. EagleCAM supports low- to high-end front camera applications with extensions for surround view, driver monitoring, and augmented reality.

Renesas Electronics Corporation

www.renesas.com

Evaluation kit for smart buildings

Infineon's XENSIV predictive maintenance evaluation kit, co-developed with Klika Tech, is powered by cloud service provider AWS to offer an end-to-end solution for smart buildings. The kit includes hardware (sensors, microcon-



troller, embedded security), software, and CloudFormation templates. It represents a perfect

starting point for quick and easy evaluation of sensor based condition monitoring and predictive maintenance. The target applications involve heating, ventilation, and air-conditioning equipment as well as motors, fans, drives, compressors, refrigeration, and other components of smart buildings.

Infineon Technologies

www.infineon.com

Compact computer-on-module

conga-TCV2 from congatec is a COM Express compact computer-on-module based on AMD Ryzen embedded V2000