

power supply, an arbitrary function generator, a digital multimeter, and an oscilloscope that use a powerful GUI, offering integrated data management and



analysis. These are connected to each other, connected to the lab, connected to the cloud, and connected to innovation to accelerate insights, whether in learning, teaching, or troubleshooting. Developed for the design and test of products in manufacturing and R&D, these offer a compact and stackable design ideal for small manufacturing businesses. Keysight's PathWave BenchVue application software complements the series, enabling quick configuration of instruments, while operating on the same PC screen to test device under test. The optional PathWave Remote Access Lab software and the PathWave Lab Manager software enhance the lab experience and productivity.

Keysight Technologies
www.keysight.com

Modules for production-line testing

Anritsu has launched TRX test module MU887002A, designed to improve the efficiency of production-line inspection of wireless communication devices,



including 5G, and space-saving universal wireless test set MT8872A. With 24 RF connectors, the TRX is a module for installation in the MT8870A and MT8872A. It supports 5G sub-6GHz New Radio (NR) RF tests and various other simultaneous wireless communications tests, including WLAN, Bluetooth, and GNSS. MT8872A is a measuring instrument designed for use in mass production and is fully compatible with the MT8870A. Its small footprint is designed to be used in narrower spaces than the standard 19" rackmount. Designed to meet the needs of manufacturers of chipsets, smartphones, wireless modules, and other wireless products, MU887002A and MT8872A save space and cut costs on production lines for wireless communication devices.

Anritsu Corporation
www.anritsu.com

ENTERPRISE-CLASS PRODUCTS

Advanced authentication solution

Modern devices are constantly exposed to the risk of counterfeit spares and accessories, compromising functionality, user safety and brand value. To solve



this problem, the OPTIGA Authenticate IDoT anti-counterfeit turnkey solution provides enhanced authentication, ECC-based security, and outstanding flexibility to address customer and application requirements. With an extended temperature range of -40 degrees to +120 degrees Celsius, the solution is ideal for industrial applications and supports the ever-growing requirements for authentication.

Infineon Technologies
www.infineon.com

Compact SMARC AI-on-module

The LEC-IMX8MP SMARC AI-on-module features NXP's i.MX 8M Plus with integrated NPU running up to 2.3



TOPS. It integrates NXP NPU, VPU, and GPU computing in a compact size for AI-based applications across industrial IoT, smart homes, smart cities, and beyond. The I-Pi SMARC IMX8M Plus is a ready-to-go IoT prototyping platform, which combines production-grade components, software portability, and Raspberry Pi-like flexibility and upgradability for proof-of-concept designs. It is the first SMARC rev. 2.1 AI-on-module that uses NXP's next-generation i.MX 8M Plus SoC for edge AI applications. The powerful quad-core Arm Cortex-A53 processor runs up to 1.8GHz with an integrated neural processing unit, delivering up to 2.3 terra operations per second for machine learning inference at the edge, suited for applications that require machine learning and vision systems paired with smart sensors to enable

industrial decision-making.
ADLINK Technology
www.adlinktech.com

Embedded GPU computer

Cincoze GM-1000 is a rugged embedded computer, configurable with MXM form factor GPUs from NVIDIA and AMD.



It is designed for equipment manufacturers, system integrators, computer vision solution providers, and end customers who need powerful, reliable computing and graphics processing for machine vision, security, autonomous vehicles, medical imaging, or edge AI applications. The GM-1000 utilises a combination of CPU and GPU computing for Artificial Intelligence of Things (AIoT) and machine learning tasks. It measures only 260mm x 200mm x 85mm for easy integration under workspaces, within devices, or on robotic arms. It features operating temperature range of -40 to 55°C, anti-shock and vibration resistance of 50G/5G, wide-range voltage input of 9V to 48V DC, over-voltage protection, over-current protection, and ESD protection. Can be configured with a wide range of storage, memory options, and OS options, including Windows and Linux.

OnLogic
www.onlogic.com

End-to-end AV over IP

Zyxel's networked AV element provides VARs, system integrators and channel



partners in the AV industry with greater scalability and efficiency. To simplify network switch installation for AV over IP, whether for one or multiple switches, Zyxel's specialised Networked AV mode integrates all the most frequently used features that are necessary to complete the job. In addition to the intuitive setup wizard, switch port and system information, bandwidth utilisation and power usage status are all graphically displayed on a single tailor-made dashboard for network administrators to manage with ease.

Zyxel Networks
www.zyxel.com