

package, reducing the bill-of-material size, cost, and complexity. It allows devices to easily track power consumption and optimise energy use by detecting reduced power efficiency for predictive maintenance, making it ideal for motor control, building automation, and a variety of green industrial applications.

Allegro MicroSystems
www.allegromicro.com

ESD protection devices

The leadless PESD2CANFDx series for CAN-FD applications, comprising DFN1412D-3 and DFN1110D-3 from Nexperia, are fully AEC-Q101-qualified, offer ESD and RF performance, and occupy 80% less PCB space than traditional SOT23 and SOT323 packages. They also feature improved thermal behaviour due to a larger internal lead frame that includes a heat-sink and thermal pad.

Nexperia
www.nexperia.com

Current sensors

The new Hall-effect based integrated current sensors, MLX91220 (5V) and the MLX91221 (3.3V) from Melexis, are meant for automotive and industrial applications such as on-board chargers, DC-DC converters, power supplies, and small electric drives.

With 300kHz bandwidth, they suit a variety of power conversion applications that require lower than 50A RMS current, resulting in a response time of just 2µs, which supports high switching frequencies and more accurate tracking in control loops.

Melexis
www.melexis.com

Power management ICs

Multi-time programmable power management ICs, the ACT88327 and ACT88329, are optimised for high performance and compact form-factor designs. They accelerate time to market by delivering design flexibility for multiple applications, from SSD cards, computer vision such as security cameras and routers, to low-power mobile uses (LPDDR5), home control, and voice-assisted devices.

Qorvo
www.qorvo.com

Z-wave SoCs

Offering seamless wireless connectivity beyond the smart home, the Z-wave 700 series SoCs from Silicon Labs, with their backward compatibility, present unique benefits of Z-wave long range for IoT applications in commercial, multi-dwelling units, and hospitality. These demonstrate one-mile point-to-point range (line-of-sight) at +14dBm output power. Additionally, the series supports dynamic output control to optimise power settings and enables up to ten years of operation on a coin-cell battery.

Silicon Labs
www.silabs.com

MODULES & BOARDS

AC-DC power supplies

The two new 120W AC-DC external power supply series from CUI provide

support for medical, dental, and general healthcare applications. These have a



small footprint, are light, and less cumbersome for use as adaptors.

The series meet 60601-1 edition 3.1 safety standards for medical uses, besides the current average efficiency and no-load power specifications.

CUI Inc.
www.cui.com

Single-phase filter

With the launch of the GTX series single-phase filters by KEMET, excess electromagnetic interference generated by power lines within 250V AC single-phase electrical systems can now be suppressed.

The filter contains a nanocrystalline core, which offers higher permeability and lower losses than ferrite material cores. As a result, the performance of single-phase power supply systems for commercial, industrial, and medical applications is improved.

KEMET
www.kemet.com

Image sensor

The new NanEyeC image sensor from ams is claimed to be the smallest, lightest 100k pixel image sensor for providing digital video output for use in mobile or wearable consumer devices like virtual



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in. Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!