

reality headsets. It enables all types of visual sensing, is GDPR compliant, connects flexibly to interfaces, and is affordable for single-use applications in consumer electronics. Combining a wide-angle view with a good depth of focus, the NanEyeC offers the speed and picture quality needed for video applications where the camera must be virtually invisible to the end-user or be accommodated in a tiny space.

ams
www.ams.com

Auxiliary AC-DC controller

In an AC-DC power supply, a secondary side microcontroller is typically unable to start it without a separate bias power supply. This problem can be solved with MCP1012



high-voltage auxiliary AC-DC controller from Microchip Technology that has the ability to remove the independent bias power supply in many applications. The MCP1012 offline auxiliary device enables the system to transfer control of the power and duty cycle to a secondary microcontroller, thus maintaining a precise and purposefully coupled control between the system and the load, which also reduces size and cost.

Microchip Technology
www.microchip.com

Power amplifier modules

The new Airfast RF power multi-chip module (MCM) series from NXP Semiconductors supports the evolution of 5G mMIMO active antenna system



requirements for cellular base stations. Based on LDMOS technology, this power amplifier module family accelerates 5G coverage and offers high output power, extensive frequency coverage, and high efficiency. The MCMs cover 5G frequency bands from 2.3 to 4.0GHz, from 37 to 39dBm average output power. A high level of integration removes RF complexities, decreases

qualification cycle time, and reduces overall development time.

NXP Semiconductors
www.nxp.com

Industrial motherboard

Avalue Technology has unveiled the EAX-W480P, an ATX board that is based on Intel 10th generation core and Celeron processors. EAX-W480P is an industrial motherboard, which



requires less expansion for automation, industrial, automatic medicine packing machines, and other embedded applications.

Avalue Technology
www.avalue.com.tw

AI development board

The WE-I Plus EVB is an endpoint AI development board that incorporates an ultra-low-power HX6537-A WE-I Plus



AI processor and HM0360 always-on image sensor. It includes an AI processor, HM0360 AoS

VGA camera, two microphones, and a 3-axis accelerometer to perform vision, voice, and vibration detection and recognition.

Himax Technologies
www.himax.com.tw

Power supply

The Protection Class II models (TPP 450BA-M open-frame and TPP 450B-M enclosed with Fan) are ideal for non-stationary requirements where a ground



connection is not possible. High efficiency up to 94% supports convection-cooled operation up to

320W at +50 degrees Celsius and 450W operation at +65 degrees Celsius with 20cfm airflow. Potential applications include portable medical equipment, home healthcare devices, and any

space-limited application where a superior power rating is required.

Traco Power
www.tracopower.com

T&M SOLUTIONS

Handheld vector network analyser

The new ZNH handheld vector network analyser from Rohde & Schwarz enables timely detection and rectification of defective RF cables and communica-



tions system components, which allows field engineers to maintain and restore

radar and satellite systems. Characterising components up to 26.5GHz in the field and lab, the analyser facilitates functions such as cable and antenna measurements and full 2-port S-parameter measurements. Useful for R&D labs, production lines, and universities with limited space and budgets, the analyser can also check RF components such as filters, amplifiers, cables, connectors, and antennas in production environments.

Rohde & Schwarz
www.rohde-schwarz.com

800G test solutions

It is challenging to meet the growing demands in network capacity due to widespread consumption of digital services delivered via wireless technologies such as 4G, 5G, and Wi-Fi. Now service



providers and data centre operators seeking 800G technology can rapidly develop next-generation data centre technologies, including 100Gb/s transmitter and receiver pre-conformance test solution with the newly launched 800G test solutions by Keysight Technologies. The solutions enable an 800G ecosystem (consisting of optical components, chipset, and switch) and IC vendors, as well as system integrators, to speed design, develop, test, and validate across the entire design cycle.

Keysight Technologies
www.keysight.com