

### Designing automatic battery testing systems is easier and faster than ever before



BT3564



1000V Maximum Input Voltage, High-Voltage Battery Tester for Measuring EV and PHEV Battery Packs

**NEW**

BT3563A



Large packs for xEVs, Large packs of up to 300 V  
Voltage measurement ranges: 6 V/60 V/300 V  
Resistance measurement ranges: 3 mΩ/30 mΩ/300 mΩ/3 Ω/30 Ω/300 Ω/3 kΩ

**NEW**

BT3562A



Large cells for xEVs, Mid-sized packs of up to 100 V  
Voltage measurement ranges: 6 V/60 V/100 V  
Resistance measurement ranges: 3 mΩ/30 mΩ/300 mΩ/3 Ω/30 Ω/300 Ω/3 kΩ

**NEW**

BT3561A



Small cells for power motors, Small packs of up to 60 V  
Voltage measurement ranges: 6 V/60 V  
Resistance measurement ranges: 30 mΩ/300 mΩ/3 Ω/30 Ω/300 Ω/3 kΩ

Measuring battery performance and safety using internal resistance (AC-IR) and open-circuit voltage (OCV)

Inspect the quality of completed cells, modules, and packs on production lines. Measure internal resistance (AC-IR) and open-circuit voltage (OCV) to check battery quality



Contact: 0124-4013811 7827978151 • Email:- [info@hioki.co.in](mailto:info@hioki.co.in) / [ravi@hioki.co.in](mailto:ravi@hioki.co.in)

Address: Unit No. 123 & 124, 1st Floor, Suncity Business Tower, Golf Course Road, Sector-54, Gurgaon – 122003, Haryana, India