


PROVIDING LED POWERED TECHNOLOGIES SINCE 1983

BINAY

LED Aviation Obstruction LIGHTS



High Intensity
200,000 candela
(Flashing White LEDs)



Medium Intensity
20,000 candela
(Flashing White LEDs)



Medium Intensity
2,000 candela
(Flashing Red
OR Fixed Red LEDs)

BINAY LED-based HIGH, MEDIUM and LOW Intensity Aviation Obstruction Light Beacons

As per International Civil Aviation Organisation (ICAO) requirements
Available in Low Intensity, Medium Intensity and High Intensity versions
(as per International Civil Aviation Organization guidelines), BINAY's patented
LED Aviation Lights come with 5-year/3-year warranties



All BINAY Aviation Lights are based on Non-switching passive type circuitry (NO SMPS)

The circuitry incorporated inside the LED Aviation Obstruction Lights is passive electronic (solid-state) in nature, and does not use internal SMPS driver switching units to control the light unit. Internal LED current control is by non-switching electronic means only. No electrolytic capacitors are used inside the Aviation Obstruction Light unit.

The above is necessary to ensure reliability of the LED Aviation Obstruction Light. This system design effectively eliminates any active components and circuits inside the aviation light itself, and enhances the solid-state passive reliability of the LEDs (mounted in relatively inaccessible locations at the height of tall structures). This drastically reduces the possibility of component failure - and hence possibility of any maintenance requirement - in the LED Aviation Obstruction Lights themselves (which are mounted at extreme heights in the system).

The BINAY LED Aviation Obstruction Light offers the following advantages:

- Fit-and-forget maintenance-free operation
- A long life of 100,000 hours (20 years at 12 hours daily burning)
- Pays for itself within a short period of operation in the form of reduced installation, maintenance and servicing costs
- Quick Installation; Reliable operation 365 days per year
- Shock-proof and vibration-resistant
- Over-Designed Intensity to allow for natural LED intensity degradation over its operating lifetime

LED Obstruction Lighting for:

- Industrial chimneys and smokestacks
- Transmission, microwave and cellular towers
- Radio, TV and similar structural towers
- High-rise buildings and structures
- Airports and airfields

THE BINAY LED OBSTRUCTION LIGHT IS UNDER ACCEPTED PATENT, AND AS SUCH IS A PROPRIETARY PRODUCT



Binay Opto Electronics Pvt. Ltd.
27, Panditia Terrace, Calcutta 700 029, India

Ph.: +91 8910624983, +91 (33) 4006 9875, 2475 0062, 2475 0030
Email: info@binayLED.com Website: www.binayled.com