

controller for automotive and industrial applications. It provides rich analogue and digital peripherals in SSOP20, TSSOP28 packages, especially suitable for small form factor applications. It could be suitable for the battery management system, automotive ultrasonic radar control, automotive lighting, automotive body control, and power applications. The series offers up to 18 I/O pins in SSOP20 and up to 26 I/O pins in TSSOP28 with optimised pin functions and features 32kB flash, 4kB SRAM, and four sets of 32-bit timers.

Nuvoton

www.nuvoton.com

Lithium-ion coin cells

The new CoinPower A4 battery cells consist of optimised electrodes, higher compression, and a new electrode balancing for higher charging voltage.

Seven different cell types with a diameter of 9.4mm × 16.1mm and capacities of 29 to 155mAh are available. The cells provide numerous possibilities for future development of wireless and mobile gear in a wide range of application areas. The lithium-ion button cells empower independence from wireless headsets, medicals to measuring and security systems as well as automotive to Industry 4.0 applications.

VARTA Microbattery

www.varta-ag.com

MODULES & BOARDS

EtherCAT modules

The ECAT-4XMO motion control and trigger module, and the ECAT-TRG4 trigger module are two new modules in the 6-CH EU series digital I/O that enable higher performance in automatic assembly, test and inspection equipment across a multitude of applications including cell phone glass inspection, battery cell assembly, camera lens assembly and test, and glue dispensing machinery as well as inspection equipment. The ECAT-4XMO is a 4-channel control and

high-speed trigger module that connects to both EtherCAT and non-EtherCAT motors while the ECAT-TRG4 includes high-speed position comparison trigger (4 channels, 10MHz linear/table), pulse outputs (12MHz), encode inputs (20MHz), and support for encoder re-driver operation. The new modules feature sliding side-by-side installation and screwless design to reduce installation costs and support nearly all field applications in a smart factory.

ADLINK Technology

www.adlinktech.com

Cellular IoT kit

The B-L462E-CELL1 Discovery kit brings together the critical hardware and software building blocks including GSMA-certified embedded SIM (eSIM)



to quickly develop power-conscious cellular IoT devices that connect to the Internet through LTE-Cat M and NB-IoT networks. It is well suited for embedded developers and IoT evangelists, and affordable for OEM and mass-market customers. The kit features an ultra-small size all-in-one cellular module from Murata, which embeds an ultra-low-power STM32L462 microcontroller, ST4SIM-200M GSMA-certified eSIM, and an LTE-M/NB-IOT chipset. The kit leverages out-of-the-box data connectivity and enables remote SIM provisioning and SIM over-the-air updates.

STMicroelectronics

www.st.com

Bluetooth based ID tag

Tag360-ID is a 43mm × 22mm × 72mm Bluetooth LE wearable identification card, designed to enable real-time location tracking and contact tracing of on-site personnel (such as employees, facility visitors, or contract staff) across indoor and outdoor facilities of all sizes including hazardous environments and restricted zones. Using Nordic's nRF52840 SoC-enabled Bluetooth LE connectivity and received signal strength indication (RSSI) capability, it can monitor its proximity to and determine interactions with other Tag360-ID ID cards, and/or Bluetooth 4.0 (and later) smartphones running the iOS/



Android 'TagStaff' app. Each Tag360-ID scans for other Tag360-ID devices in its vicinity and based on the RSSI signature and duration of the contact, records 'contact events' between tags.

TagBox

www.tagbox.co

Single-board computer

The IB953, a 146mm × 102 mm single-board computer is powered by 11th Gen Intel core processors and offers impressive I/O and computing performance, making it an ideal platform for a broad



range of demanding applications in factory automation, machine vision, healthcare, as well as retail environments. It features a 5G compatible M.2 3052 socket with the latest Intel processors built on 10nm SuperFin process, delivering up to 25% faster performance and greater AI acceleration. IB953 supports high-speed interfaces to deliver reliable processing for business-critical data operations with 2x SATA III, 3x USB 2.0, 3x USB 3.1, 2x COM, and 3x M.2 sockets (NVMe and CNVi supported). Additionally, it features 2x GbE ports, 2x DDR4-3200 slots, TPM (2.0) data encryption technology, ErP/EuP energy-saving function, and a wide-range 12 ~ 24V DC power input suitable for different industrial applications.

IBASE Technology

www.ibase.com.tw

Audio streaming device

The OtterCastAudioV2, an open source audio streaming device, is based on a Sochip S3 SoC. It supports AirPlay web interface, Shairport Sync, Snapcast, Spotify Connect, and PulseAudio sink/source, allowing synchronised multi-room audio with the power of Ethernet. The firmware is built using Buildroot, a simple, efficient, and easy-to-use tool to generate embedded Linux systems through cross-compilation. It includes S3 128MB DDR3 1.2GHz single-core Cortex-A7 and has SDIO Wi-Fi + BLE, 100BASE-T, USB-OTG connectivity feature. OtterCastAudio also features an integrated headphone amplifier (30mW into 32Ω, 60mW into 16Ω).

Ottercast

<https://cast.otter.jetzt>

