

Compressor reference boards

For rotary refrigerator compressors, two new reference boards have been designed. Both are turnkey solutions for low-power compressors that can be used for building final mass-production application boards.

Since the design of the reference boards is system tested, developers can drastically reduce their own system development time. The REF_Fridge_D11T_MOS is a ready-to-use three-phase inverter that provides an easy-to-use power stage based on the digital motor control iMOTION smart driver. The REF_Fridge_C101T_IM231 is ideal for customers aiming for a higher level of integration and a reduced footprint. A combination of an iMOTION IC IMC101T-T038 with a 3-phase CIPOS micro intelligent power module offers a compact inverter solution for low-power motor drive applications.

Infineon Technologies
www.infineon.com



operating temperature range of -40°C to +125°C, with 100% available power at 100°C baseplate temperature.

Flex Power Modules
www.flexpowermodules.com

I/O card for digital signals

The new Digital I/O card offers engineers and scientists a cost-effective way to generate and acquire fast digital signals. The model M2p.7515-x4 is a half-length PCIe card that measures just 168 mm × 107 mm.



The tiny form factor means that it can be inserted into almost any desktop PC, turning it into a powerful tool for applications such as logic analysis or pattern generation. The card features 32 parallel channels that can be clocked at speeds up to 125MHz. Designed for maximum versatility, the cards come with 1GB on-board memory as standard and a variety of different acquisition and replay modes.

Spectrum Instrumentation
www.spectrum-instrumentation.com

clearly seeing signals with an unbanded, preselected sweep from 2Hz to 110GHz and up to 11GHz analysis bandwidth.

Keysight Technologies
www.keysight.com

Mixed-signal scopes

The PicoScope 6000E series mixed-signal oscilloscopes (MSOs) have four new 4-channel models, each of which can be configured with 16 optional digital channels. With bandwidths of 750MHz or 1GHz, 8-bit or 8/10/12-bit flexible resolution, and up to 4GS deep



capture memory, these enhance the existing PicoScope 6000E portfolio comprising 350MHz and 500MHz models. The new compact oscilloscopes deliver a cost-effective test and debugging solution for engineers, developers, and scientists working on high-performance digital and mixed-signal designs.

Pico Technology
www.picotech.com

Converter for RF power amplifier

The BMR685's power-handling capabilities make it well-suited to high-power RF power amplifier applications, for both LDMOS and GAN needing a 50V rail. The new converter provides high efficiency of up to 97.2% at half load. It has an output voltage range of 25V to 55V and can deliver up to 26A output current. Its input voltage range is 36V to 75V, and isolation between input and output is 2,250V. The BMR685 includes digital functionality, accessed over a PMBus interface, which enables easy monitoring of temperature, voltage, and current, as well as simple adjustment of output voltage. The converter has an



T&M SOLUTIONS

mmWave signal analyser

Enabling the test of millimeter-wave (mmWave) innovations in 5G, aerospace, defense, and satellite communications is the new N9042B UXA X-series signal analyser that provides wide analysis bandwidth and deep dynamic range to help customers



solve their most difficult mmWave challenges including tight design margins and timelines, complex modulation, and stringent standards. It ensures that designs meet the latest standards with ready-to-use measurement applications and signal analysis software while

Single/dual power supplies

The new R&S NGA100 series provides a choice of single and dual outputs with up to 35V/6A per output, or 100V/2A per output. Single output models supply up to 40W, dual output models up to 80 W power. The dual model outputs can be



combined to provide up to 200V or 12A. A linear design has been implemented throughout the output circuits, which significantly improves performance. The resulting higher accuracy means engineers can be confident of supplying exactly the right power level without any need for an additional multimeter. The standard level of readback resolution, 1mV/100µA, is enhanced for currents under 200mA



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?
Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!