

solid state relay (SSR) that has a high current capacity (1A, 60V) and integrates both current limiting and thermal shutdown circuits. It provides a rugged solution for demanding applications, which is not



the case when using electro-mechanical relays and standard SSRs. Applications include smart homes, automation, and battery-powered systems.

Littelfuse

www.littelfuse.com

New-tech DRAM

Claimed to be built using advanced DRAM process technology, the 1 α (1-alpha) node DRAM-based products offer major improvements in bit-density, power, and performance. The



applications for this new DRAM technology enhance performance in products,

from mobile devices to smart vehicles. A low-power mobile DRAM, with a 15 per cent improvement in power savings, allows 5G mobile users to perform more tasks on their smartphones without sacrificing battery life.

Micron Technology

www.micron.com

Cellular and GNSS SiP

The ALEX-R5, a miniature cellular module integrates low-power wide-area (LPWA) connectivity and global navigation satellite system (GNSS) technology into an ultra-small system-in-package (SiP) form factor. It has a 23dBm cellular transmission power that allows end-devices to operate effectively in all signal conditions, whether at cell edges, underground,



or in other challenging scenarios. The device is optimised for power-sensitive and battery-dependent applications such as wearables and connected medical devices.

u-blox

www.u-blox.com

IoT-based SoC

The RSL10 SoC now comes with the low power Flash-based Bluetooth Low-Ener-



gy radio that allows designing of ultra-low-power indoor asset tracking applications with direction finding features

and advanced angle-of-arrival (AoA) technology. Its unique direction finding methodology and positioning algorithms enable real-time tracking of tags and devices, with centimetre-level accuracy even in challenging environments.

ON Semiconductor

www.onsemi.com

Integrated GaN device

The MasterGaN2 delivers an integrated gallium nitride (GaN) solution suited to soft-switching and active-rectification converter topologies. The 650V nor-



mal-off GaN transistors have on-resistance (RDS(on)) of 150m Ω and 225m Ω . MasterGaN2 further extends the efficiency gains,

size reduction, and weight savings of topologies such as active clamp fly-back. The MasterGaN power system-in-package (SiP) family combines the two GaN high-electron-mobility transistors (HEMTs) and associated high-voltage gate drivers in the same package with built-in protection mechanisms.

STMicroelectronics

www.st.com

AC-DC converters

Two AC-DC converters, the RAC02E-K/277 and RAC03E-K/277, rated at 2W and 3W respectively, include inputs of 100V AC up to 277V AC for use



in a wide variety of applications. Regulated outputs include 3.3V, 5V, 12V, 15V, and 24V

without derating up to 80 degrees Celsius (RAC02E-K/277) or 75 degrees Celsius (RAC03E-K/277).

RECOM

www.recom-power.com

MODULES & BOARDS

Condition monitoring platform

The CN0549 is a condition-based monitoring (CbM) development platform that provides mechanically-secure, wide-bandwidth sensor data with robust, high-fidelity data acquisition for



condition-monitoring. Its open source software simplifies connectivity from

embedded systems to popular data analysis tools. For predictive maintenance, the platform enables real-time vibration data processing for rapidly developing machine learning algorithms.

Analog Devices

www.analog.com

In-car safety solution

Providing vehicle and passenger safety using 4D imaging is a new single-chip solution powered by a single sensor. The solution comes with child presence detection (CPD) and seat belt reminder (SBR) features. This has been made possible by a large antenna array and



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!