

an ultra-wide field-of-view with the help of multiple transceivers that offer



a high resolution for rich detection and data classification of occupants. Powered by a single radar-on-chip (RoC), the solution replaces numerous existing in-car sensors, covering a full vehicle cabin, and detecting and classifying all occupants in all lighting conditions.

Vayyar
www.vayyar.com

DC-DC converter

The BMR492 series of digital eighth-brick intermediate bus converters provide a 'burst mode' operation



required for data-com CPUs and data centre applications. Capable of delivering continuous power between 600 and 800W, along with a peak power of up to 1100W for short periods < 1s, the new BMR4920302/861 converter delivers a 12V output. Rated to a maximum 600W output over an input voltage range of 40-60V, the DC-DC step-down solution is ideal for nominal 48 or 54V input voltage systems.

Flex Power Modules
www.flexpowermodules.com

AC-DC power modules

The PAA and PAAM series of AC-DC encapsulated power modules are ideal for space-constrained industrial and



medical applications. Available in power ratings ranging from 5 to 150 watts, the PAA encapsulated modules boast of exceptional conversion efficiencies of up to 89 per cent. The PAAM encapsulated power modules are available in 15 to 150-watt options and maintain conversion efficiencies as high as 93.5 percent. The PAA series is suitable for industrial applications while the PAAM series is ideal for portable medical devices and wider medical equipment.

TT Electronics
www.ttelectronics.com

Development board

The new Raspberry Pi Pico offers exceptional performance thanks to being built



around the Raspberry Pi RP2040 microcontroller, delivering a flexible, highly affordable development platform that can be directly deployed into end products. RP2040 offers high performance for integer workloads, large on-chip memory, and a wide range of I/O options, making it a flexible solution for a wide range of microcontroller applications.

Raspberry Pi
www.raspberrypi.org

Power supply

The Protection Class II models (TPP 450BA-M open-frame models and TPP 450B-M enclosed with fan models) are ideal for non-stationary requirements where a ground connection is not possi-



ble. Potential applications include portable medical equipment, home health-care devices, and space-limited devices. High-efficiency up to 94 percent supports convection-cooled operation up to 320 watts at +50 degrees Celsius and 450 watts operation at +65 degrees Celsius with 20cfm airflow.

TRACO POWER
www.tracopower.com

T&M SOLUTIONS

Data acquisition system

The DL950 ScopeCorder, a high-precision data acquisition system, enhances the functionality and operability of new product development in the automobile, mechatronics, and electronics industries.



ScopeCorder series data acquisition systems combine the functions of oscilloscopes and data recorders for wide use in the development and maintenance of mechatronic equipment. Up to five DL950 units can simultaneously measure and display weight, pressure, displacement, vibration, torque and

other parameters for data analysis.

Yokogawa
www.yokogawa.com

Generator and digitiser

The hybrid NETBOX series combines a multi-channel arbitrary waveform generator (AWG) and a digitiser a single portable unit. Capable of simultaneous signal generation and acquisition,



the tool is ideal for stimulus-response or closed-loop type testing. The series offers two or four AWG channels combined with the same number of digitiser channels that generate almost any waveshape using high-resolution, 16-bit digital-to-analogue converters (DAC).

Spectrum Instrumentation
www.spectrum-instrumentation.com

Signal quality analyser

The MP1900A series of high-quality bit error rate tester (BERT) for evaluating next-generation 400 and 800GbE high-speed devices and transceivers now comes with a new FEC analysis function that detects FEC symbol errors



based on the 400GbE FEC standard. Using this new function, changes in bit errors and FEC symbol errors having changes in input amplitude and jitter conditions can be monitored in real time.

Anritsu Corporation
www.anritsu.com

Vector signal generator

The new SMM100A vector signal generator displays excellent RF characteristics across the entire frequency range from 100MHz to 44GHz, covering all the bands used by wireless standards,



including LTE and 5G NR, as well as the latest WLAN standards Wi-Fi 6 and Wi-Fi 6E (up to 7.125GHz). Wireless personal area networks, such as Bluetooth, are covered as well. The SMM100A features a large ARB memory depth of up to two Gsamples and a