

COMPONENTS

Non-volatile SRAM

The second-generation non-volatile static RAMs (nvSRAMs) are qualified for QML-Q and high-reliability industrial specifications and data-logging applications in harsh environments, including aerospace and industrial applications. The 256kb STK14C88C and 1Mb STK14CA8C nvSRAMs come in both 5V and 3V versions. In the event of a power failure, the nvSRAM automatically saves a copy of the SRAM data into non-volatile memory, where the data is protected for over 20 years.

www.infineon.com

POL switching regulator

The TSR 1.5E is a 1.5A step-down switching regulator series that suitably replaces older, inefficient industrial step-down regulators. It has a wide input operating range of 7-36V DC. It offers a high efficiency of 97%, better output accuracy, lower standby current, and no requirement of external capacitors. The series offers a broad application range in environments to reduce production cost by delivering not only a highly cost efficient but also reliable solution.

www.tracopower.com

Varistors for surge protection

The LST varistor series incorporates both a built-in thermal disconnect function and electric arc shield, which provides additional robust protection to

prevent catastrophic failure and fire hazard under extreme overvoltage conditions or varistor end-of-life. Applications include industrial infrastructure, UPS, industrial motor control, and HVAC system. It is specifically designed for Type 1 and Type 2 surge protective devices.

www.littelfuse.com

Magnetic encoder ICs

The AEC Q100 (Grade 1) qualified magnetic encoder ICs, iC-MU200 and iC-MHL200, are suitable for high-precision hollow shaft and off-axis rotary




measurements. These can also be used in electrically commutated motors for measuring steering angles, in lidar applications or for general angle detection applications. Temperature range is from -40°C to +125°C. The iC-MU200 is suitable for applications that require absolute position information right after switching on the encoder system. For incremental applications, iC-MHL200 is well suited.

www.ichaus.de

Breakthrough electronic switch

The new MM5130 enables significant reductions in distortion for RF systems and delivers up to 10,000x improvement over existing RF electromechanical relays and solid-state switches. Enhanced IP3 performance results in size, weight, power, and cost improvements



as power amplifiers and other RF components can be scaled back in power and reduced in size, ultimately enhancing overall system performance. This makes the MM5130 switch optimal for

advanced RF systems including low-loss switched filter banks, tunable filters, step attenuators, RF and microwave switching in radio front-ends, phase shifters for beam steering, and phased array antennas used in 5G networks.

www.menlomicro.com

Coreless current sensor

The new coreless Hall-effect current sensor ACS37610 is built for demanding automotive and industrial systems, offering higher accuracy and sensitivity, additional fault detection capabilities, and user



programmability. The sensor's 250kHz bandwidth, dedicated

overcurrent and overtemperature fault pin, and a slew of built-in diagnostics make it ideal for safety-critical applications. It also features advanced differential sensing technology, resulting in greater signal-to-noise ratio.

www.allegromicro.com

Low-power MEMS oscillator

The SiT8008 low-power MEMS oscillator can now operate at any voltage between 1.62V and 3.63V, suiting industrial and medical applications such as factory automation, seismic sensing, and data acquisition that use many clock sources in a single system. Along with continuous voltage operation, the SiT8008

also offers industry-leading resilience and reliability, a wide programmable frequency range with six decimals of accuracy, low power consumption, small package size, and short lead times.

www.sitime.com

Intelligent edge application devices

The new Artix and Zynq UltraScale+ devices now address a wider range