

of a smartphone, allowing customers to pack more power into an application without having to increase the size of the module. The module is ideal for a wide range of high-voltage applications including medical devices, unmanned aerial and terranean vehicles, and industrial applications where extreme heat and cold are a significant factor.

www.artesyn.com

Power supply for demanding applications

The PCA1500F, a 1500W power supply, delivers extended communications I/O for demanding medical and industrial applications. Complying with stringent medical standards EN/IEC 60601-1, it features



a reinforced input to output isolation of 4,000V AC and a grade of 2x Means of Patient Protection (2xMOPP). The PCA series offers a universal input voltage of 85V to 264V AC. Exhibiting flexibility, the output can be operated in constant voltage or constant current mode with either analogue or digital control.

www.cosec.co.jp

Isolated DC-DC converters

The 0RQB-C5W24x and 0RQB-C5W54LC board-mount, isolated DC-DC converters provide up to 162W output power from a wide input range. Specifications include an output voltage of 24V and 54V DC and an input voltage range suitable



for 72V, 96V, and 110V nominal battery voltages. Conformal coated PCB is used for environmental ruggedness, making this DC-DC converter series ideal for industrial, railway, and telecommunication industries and applications. PoE applications supporting the IEEE 802.3af standard for power transmitted over LAN cables are also ideal for this converter series.

www.belfuse.com

Evaluation board for HMIs

To assist with the initial development and prototyping of human machine interfaces (HMIs) based on object-oriented graphic controller ICs, Bridge-tek has announced availability of the ME817EV



evaluation board. Featuring the company's BT817 embedded video engine (EVE) device, it allows engineers to experiment with the latest generation of EVE technology and get a comprehensive understanding of the breadth of its capabilities. Thanks to the higher resolutions and large format displays that the BT817 supports, more compelling and functionality-rich HMIs can be created with greater visual clarity and enhanced video playback capabilities.

www.brtchip.com

5G module for automotive use

The UMNZ1 series 5G NR module featuring ultra-fast speeds, ultra-low latency, and mass connectivity when used in combination with vehicle-to-everything systems,



gives vehicles the capability to communicate and interact with everything around them such as road infrastructure, other vehicles, and pedestrians. It also spurs integration of IoT technology that can improve the efficiency of car maintenance and inspections by keeping an eye on the condition of a vehicle via a range of different sensors.

www.alpsalpine.com

Industrial compute module

Combining industrial grade hardware with Raspberry Pi's is the latest CM4 compute module that offers the ability to reliably deploy ARM compute power into factories, warehouses, and a wide range of



IoT applications. The device integrates visible aluminium heat-sinks, which not

only provides efficient fanless cooling but also protects internal components.

www.onlogic.com

T&M SOLUTIONS

Vector network analyser

The R&S ZNA, a touch-operated vector network analyser, now covers frequency ranges of up to 50GHz and 67GHz. It



features excellent RF performance, including wide dynamic range and extremely low trace noise,

and comes with a user-friendly, purely touch based GUI. Its unique hardware platform offers up to four internal, phase coherent sources plus a fifth source which can be used as a second internal local oscillator or as an additional source for measurements on mixers.

www.rohde-schwarz.com

Signal generator for qubits

The SHFSG signal generator, a first instrument of its kind, can output signals from DC up to 8.5GHz without the



need for mixer calibration and provides spurious-free, low-noise signals in 1GHz bandwidth. Specially designed for superconducting and spin qubits, the signal generator takes advantage of the double super-heterodyne frequency conversion technique to ensure better linearity and fewer spurious tones. It can be programmed to generate complex gate sequences.

www.zhinst.com

Industrial Ethernet tester

The LinkIQ Cable + Network tester combines switch diagnostics with state-of-the-art cable measurement technology and provides simple pass/fail test reports using the LinkWare software. It can also verify the performance



of switches including those that provide power over Ethernet. For an open cable, the device shows the length and pairing. If it's terminated with the supplied