

remote, the test result shows the maximum data rate the cable can support – up to 10Gb/s.

www.flukenetworks.com

AWG and digitiser combo

The hybridNETBOX is an innovative instrumentation platform that combines a multi-channel arbitrary waveform generator (AWG) and a digitiser in a single portable unit. With a unique capability for simultaneous signal generation and acquisition, this powerful tool is perfect for applications involving stimulus-response or closed-loop type testing. The AWG channels can generate almost any waveshape thanks to their use of the latest, high-resolution 16-bit digital to analogue converters.

www.spectrum-instrumentation.com

3-phase AC emulator for EVs

The SL1200A series Scienlab regenerative 3-phase AC emulator is a comprehensive solution consisting of hardware, software, consulting, and support services for EV and electric vehicle supply equipment charging applications and grid-edge applications. The series handles 3-phase AC test requirements of up to 1,200V AC, from 30kVA to 630kVA, without the need for a transformer.

www.keysight.com

High-speed laser sensor

The AR550 high-speed laser sensor is a fast triangulation device for dimensional and distance measurement. At sampling rates up to 70kHz, these sensors are typically used for applications that demand high speed such as vibration measurements, scanning of roads, vehicle crash test, and ballistic measurements. The AR550 comes in one compact package size with nine different measurement ranges and can transmit its highest sampling rates via Ethernet output.

www.acuitylaser.com



MANUFACTURING EQUIPMENT

Reliable magnetic gripper

The MG10, an easy-to-use magnetic gripper for material handling, assembly, and machine tending applications in manufacturing, automotive, and aerospace environments offers a unique adjustable force and grip detection that provides unprecedented control levels. The device comes with built-in grip and sensors for part detection. And if the robot loses power or has to make an e-stop while performing a task, there is no risk of dropping the part being handled. The MG10 also provides precise and durable handling of objects with abrasive, uneven, or perforated surfaces.

www.onrobot.com

Intelligent placement modules

Two highly innovative and intelligent new placement modules, the Europlacer ii-A1 and ii-A2, boost placement



productivity. The ii-A1 features a single Tornado turret head, offers speeds up to 15,000cph and can be deployed for specific SMT assembly duties. The ii-A2 is equipped with a pair of high-speed Pulsar pipette heads, offers placement speeds up to 50,000cph and provides a component inventory of 164x8mm feeder positions to deliver a fast, fully intelligent, and highly integrated boost to line throughput.

www.europlacer.com

CHEMICALS & ADHESIVES

UV-reactive adhesive solution

The new AU588 solution focuses on 'by-the-dot' bonding and gasket applications required in the development of consumer electronics and automotive manufacturing including advanced

driver-assistance systems and engine control units. It is UV-reactive, features high seal performance, and excellent



elasticity. It also displays long durability in high-temperature environments and excellent hydrolysis resistance, along with high elongation and high tensile strength when exposed to a great compression ratio.

www.bostik.com

SOFTWARE

Multi-board design software

The Proteus v8.12 enables fast and accurate development of high-speed differential pair signals with automatic skew correction, target length matching, and dedicated reporting features. It also supports multi-board design per project, where a single schematic encompasses the design logic for multiple PCBs. Documentation outputs such as the bill of materials and production outputs such as Gerber X2 are all board-aware.

www.labcenter.com



ENTERPRISE-CLASS PRODUCTS

Infrastructure resiliency solution

The TimeProvider 4100 Release 2.2 Grandmaster provides a new level of resiliency via software with the introduction of an innovative redun-



dancy architecture, enabling flexible deployment and lower hardware costs without sacrificing ports. Additionally, it supports a multiband GNSS receiver to protect against time delay resulting from space weather, solar events, and other disruptions that may impact critical infrastructure services. An enhanced security ensures always-on precise timing and synchronisation.

www.microchip.com