

ing stage uses an LLC resonant topology deploying the latest generation of power semiconductors, with a typical efficiency of up to 95%.

COSEL

www.cosel.co.jp

mmWave module

The PRM2141 IEEE802.11ad/ay module is fully tested to an over-the-air antenna input/output specification, thus relieving OEMs from the complexities of ensuring the integrity of the mmWave RF performance. In terms of performance, the phased array antenna is optimised for both as standalone device and for use with a parabolic reflector. Using a 40cm dish antenna, it links up to 25km. In standalone configuration, the module supports a range of more than 500m. Applications include PtP and PtMP links for fixed wireless access networks, private mmWave networks, 5G base station backhaul, and V2X communications.

Peraso

www.perasotech.com

Development kit

The S-2CONNECT Creo development kit with LTE Cat M1/ NB-IoT is designed to accelerate digital programs. The kit is designed for software developers who are charged with reducing R&D risk and fast-tracking their IoT application development. The kit includes the S-2CONNECT Creo system-on-module, an evaluation board, and accessories, and comes with a 3-month cellular subscription.

TT Electronics

www.ttelectronics.com

Computer-on-module

The new 11th Gen Intel core processor based computer-on-module with soldered RAM is built for high shock and vibration resistance in challenging transportation and mobility applications. It can withstand temperature ranges of -40°C to +85°C. The module offers



significantly greater CPU performance and nearly 3x higher GPU performance compared to the predecessors, along with state-of-the-art PCIe Gen4 support.

congatec

www.congatec.com

Wi-Fi 6 based module

The i.MX 8 system on module (SoM) with Wi-Fi 6 brings performance improvement with increased spatial and spectral performance in high-density environments, targeting connected industrial, medical, and automotive applications. With Wi-Fi 6 integrated on the SoM, it becomes easier for designers to design carrier cards and end products, shortening development time with reduced risk and complexity.

iWave Systems

www.iwavesystems.com



T&M SOLUTIONS

Fully integrated oscilloscope

The all-new R&S RTO6 digital oscilloscope offers six different bandwidth models from 600MHz to 6GHz and up to 20 giga samples per second. The fully integrated test solution for the time and frequency domain, as well as as protocol and logic analysis, supports design engineers from all industries. It features a high waveform update rate, excellent signal fidelity, a uniquely powerful digital trigger, responsive deep memory, and full HD screen, with easy-to-use touch functionality.

Rohde & Schwarz

www.rohde-schwarz.com



Intuitive signal generator

The SGX1000 RF signal generator is a new series of instruments that combine high performance signal generation capabilities with an intuitive user interface. The unique, proprietary blend of direct digital and direct analogue synthesis enables ultra-fine frequency resolution, lightning-fast frequency switching, ultra-low phase noise and jitter, and



superior reliability. The SGX1000 series brings high-performance signal generation at an affordable price for broad use in the semiconductor, military, aerospace, medical, and communications industries.

Wireless Telecom Group

www.wirelesstelecomgroup.com

Protocol analyser

The Frontline X500 wireless protocol analyser is a one-box solution that provides time-correlated captures of Bluetooth Basic Rate, Extended Data



Rate, Low Energy, Wi-Fi 6E (802.11ax), and 802.15.4 based technologies such as Zigbee and Thread. The instrument delivers reliable capture, decryption and decoding in complex multi-technology test environments, with market-leading support for the latest Wi-Fi technologies, helping to reveal potential issues, errors, interference, or conflicts in the wireless trace, as well as to identify device performance enhancement opportunities.

Teledyne LeCroy

www.teledynelecroy.com

Automotive radar tester

The new R&S RTS radar test system consisting of the R&S AREG800A backend and the R&S QAT100 antenna array frontend is a target simulator that generates dynamic radar echoes. It can be used at all stages of automobile radar sensor testing—from pre-development through hardware-in-the-loop lab tests to validation of ADAS/AD functions integrated in the vehicle. The system simulates the radial velocity (Doppler shift) and the size (radar cross-section) of objects at very small ranges, allowing early error detection.

Rohde & Schwarz

www.rohde-schwarz.com



SOFTWARE TOOLS

Microcontroller design tools

The new MPLAB cloud tools ecosystem for PIC and AVR devices makes microcontroller design easy. The free, all-in-one cloud platform combines