

easy, integrated search and discovery of example code, graphical configuration of projects, and code debugging in a collaborative environment, enabling rapid development while simplifying software design for users at all skill levels with an intuitive browser based interface and cloud connectivity.



Microchip Technology
www.microchip.com

Updated STM32Cube Software

The X-CUBE-IOTA1 expansion software package includes IOTA-specific middleware and sample implementations for the STM32Cube microcontroller (MCU) software development ecosystem. It allows developers to benefit from the efficient performance and high feature integration of STM32 MCUs for building smart, connected transaction-handling devices that leverage the latest Chrysalis upgrades to the IOTA DLT, which is a decentralised secure database that protects against data tampering.

STMicroelectronics
www.st.com

Embedded development tool

The complete development toolchain IAR Embedded Workbench for RISC-V adds support for the latest Andes RISC-V extension and devices, enabling maximised performance in RISC-V based applications. It helps developers ensure the application fits the required needs and optimises the utilisation of on-board memory. It is a complete C/C++ compiler and debugger toolchain with everything embedded developers need integrated in a single IDE.

IAR Systems
www.iar.com

Source code debugger

The Tracealyzer version 4.5 provides support for the Espressif ESP32 MCU and open source Zephyr RTOS, along with improving the integration with



Lauterbach uTrace, and more. The new version offers improved support for the STLINK-V3 debug probe. It also includes support for Percepio DevAlert, a cloud service for monitoring and remote diagnostics of IoT devices during testing and deployment.

Percepio
www.percepio.com

MANUFACTURING EQUIPMENT

PCB plasma treatment system

The MARCH MegaVIA plasma treatment system with a 15-cell configuration for panel sizes up to 76.2cm x 132.1cm during PCBs manufacture offers high process reproducibility and plasma treatment uniformity for PCB panels. The MegaVIA system provides plasma treatment at 40kHz and accommodates all common gases - CF₄, oxygen, nitrogen, and argon. An EPC controller with intuitive Windows 10 PC based touchscreen HMI allows for a wide range of data collection and control capabilities.



Nordson Electronics Solutions
www.nordson.com

CHEMICALS & ADHESIVES

Soldering flux

Providing solutions for current and evolving industry challenges is the new TACFlux 571HF, a no-clean, halogen-free flux formulated for both hand soldering and rework. It is compatible with typical lead-free (SAC) as well as low-temperature bismuth- and indium-containing alloys for PCB assembly applications. Besides being halogen free, other benefits include post-reflow flux residue clearing for no-clean applications and shelf life of up to one year.



Indium Corporation
www.indium.com

Reworkable underfill adhesive

Structalite 5751 is a black, heat-curing, resin-based epoxy adhesive characterised by low viscosity and linear flow behaviour. The uncured properties

of Structalite 5751 allow contactless dispensing for fast and precise placement of the adhesive. This underfill has a low ion content and is well suited for electronic component packaging, despite its black colour. It allows manufacturers to reduce both manufacturing costs and environmental impact by reusing electronic components mounted on PCBs.

Panacol-Elosol GmbH
www.panacol.com

ENTERPRISE CLASS

Multiport PoE injector

Multiport Power over Ethernet (PoE) power sourcing equipment (PSE) injector, also known as a midspan, enables any multigigabit switch to support a device's high power needs and data rates, with no network configuration or downtime necessary. Multigigabit PoE-enabled switches with sufficient power for Wi-Fi 6 devices and small cell equipment are expensive and not widely adopted. A more cost-effective way to inject power into the network for these high-speed devices is to install one of Microchip's new multiport, multigigabit midspans between them and any standard multigigabit switch.



Microchip Technology
www.microchip.com

Data centre SSD

The DC1500M, a U.2 data centre NVMe PCIe SSD for mixed-use workloads leverages a high-performance Gen 3.0 x4 PCIe NVMe design. It delivers predictable random IO performance as well as predictable latencies over a wide range of workloads. The drive delivers consistent read/write latencies of < 110µs / < 206µs, respectively. Additionally, adopting the U.2 form factor allows current Gen 3.0 and Gen 4.0 servers and storage arrays to immediately utilise existing PCIe slots and U.2 backplanes while maintaining serviceability with hot-pluggable drives.



Kingston Technology
www.kingston.com