


monitoring defined areas in transport and logistics applications.

Acuity Laser

www.acuitylaser.com

Tiny magnetic transducer buzzer

The CMT-322-65-SMT-TR is a 3.2mm × 3.2mm magnetic transducer buzzer, making it among the smallest micro



buzzers in the industry. It features a low profile of 2mm, surface mount packaging, and a

sound pressure level (SPL) of 65dBa at 10cm. Ideal for portable equipment applications and space-constrained designs, this magnetic audio transducer carries a rated voltage of 3Vo-p, low current consumption of 120mA, and a rated frequency of 4kHz. It also offers an operating temperature range of -20 to 70°C and reflow solder compatibility.

CUI Devices

www.cuidevices.com

Battery management IC

The MAX17330 battery management IC with integrated fuel gauge and advanced battery protection for one-cell lithium-ion/polymer batteries claims longer bat-



tery runtime for consumer applications than similar products. It significantly extends run-time and monitors internal cell self-discharge hazards, while also shrinking the solution size of single-cell-battery-powered products. MAX17330 simplifies battery management for devices using parallel cells such as foldable smartphones and tablets, AR/VR smart glasses, and medical and fitness wearables.

Maxim Integrated

www.maximintegrated.com

Security chips for connected cars

The Sm@rtSIM CX Luna1.3M is a next-

generation industrial and automotive grade product suite that is based on Infineon's newest security controller



SLI37, which meets the technical specifications of the automotive industry and is specifically tailored to the challenging environmental conditions of automobiles. With a faster CPU and larger memory, they enable several innovative applications for the connected car. The new products based on these controllers allow automotive manufacturers to provide highly secure and high-performance mobile connections via eSIM technology. They support 5G standalone networks and cover all eSIM consumer and M2M use cases.

Giesecke + Devrient

www.gi-de.com

Capacitive hidden switch

This capacitive hidden switch can be mounted behind the surface of non-conductive materials and is therefore invisible.



With capacitive switches, an electric field is built up on the user surface of the sensor.


With this direct sensor contact with the finger to trigger is no longer required. The electrical field change required to trigger the switching process is achieved even if a non-conductive material (glass, plastic, wood, or similar) is there between the sensor and the finger.

SCHURTER

www.schurter.com

Automotive LED lighting ICs

The A80803 is a switch-mode, constant-current controller for high-power LED automotive lighting applications. It leverages



multi-topology conversion and patented IP to enable smooth high/low/high beam

transitions in a single IC. The A80804 is a four-channel linear LED driver that provides high power for automotive lighting applications through multiple, independently-configurable channels. Its low EMI output helps it achieve CISPR25 Class 5 compliance. Both products help designers reduce the number of ICs required to create safety-enhanced automotive lighting systems, enabling higher performance and compact designs at lower cost.

Allegro MicroSystems

www.allegromicro.com

Bidirectional buck/boost converter

The TPS61094 is a bidirectional buck/boost converter with an ultra-low quiescent current (IQ) of 60 nA—one-third the



IQ of competing boost converters. It integrates a buck mode for supercapacitor charging while providing

ultra-low IQ, enabling engineers to extend battery life by as much as 20% when compared to commonly used hybrid-layer capacitors. Supercapacitor charging and discharging helps support peak loads and backup power, which are important for continuous operation in battery-powered industrial applications such as smart meters, smoke detectors, video doorbells, and medical applications.


Texas Instruments

www.ti.com

MODULES & BOARDS

Compact Bluetooth SiP

The ANNA-B4 module is a feature-rich, ultra-compact Bluetooth 5.1 system-in-package (SiP).



It targets applications in harsh environments such as smart lighting networks and industrial circuit breakers as

well as indoor positioning use cases in manufacturing sites, warehouses, hospitals, and smart cities. Measuring 6.5mm × 6.5mm, including its integrated antenna, it combines the Nordic nRF52833 chipset's feature set with