

output from 5 to 30V (RPMA-4.5) or 3.3 to 16.5V (RPMA-8.0). The cost-effective parts feature high efficiency, peaking



only and up to +85°C with derating/airflow, depending on input/output conditions. On/off control is included along with remote output sensing. The RPMA-4.5 and RPMA-8.0 are fully protected against input under-voltage, output over-current, short-circuit, and over-temperature.

RECOM Power
www.recom-power.com

USB-PD reference design

The new active clamp flyback (ACF) based reference design that will simplify and speed the development of 65W 1C fast charger applications is built around Silanna's SZ1131 ACF controller and incorporates Transphorm's Super GaN FET. It is a production-ready 65W 1C USB-PD reference design for travel adapters and battery chargers. The reference design delivers industry-leading peak efficiencies of 94.5% and flat efficiency across universal (90 to 265V AC) input voltages and loads. No-load power is just 23mW@230V AC and the design measures only 34.5mm × 34mm × 30.5mm (giving it an uncased power density of 30W/inch³).

Silanna Semiconductor
www.powerdensity.com

Compact DC-DC converters

The new TEN-WIRH range of 3 ~ 40W high-reliability DC-DC converters come in compact and fully encapsulated footprints with an ultra-wide 4:1 input range of 36 ~ 160V DC. The series includes five power platforms covering 3/6/10/ 20/40W power levels with



single and dual outputs ranging 3 ~ 24V DC and high efficiency operation up to 90%. All models feature 3,000V AC reinforced I/O isolation, an internal filter for EN 50121-3-2 compliance (EMC for Rolling Stock), remote on/off control, and embedded protection from under-voltage input, short-circuit, over-temperature, and over-voltage conditions. The proven and certified design guarantees highest resistance against thermal shocks, moisture, mechanical shocks, and vibration.

TRACO POWER
www.tracopower.com

T&M SOLUTIONS

Microwave measurement receiver

The R&S FSMR3000 is a microwave measurement receiver that can calibrate signal generators and attenuators with one single instrument. Most important features provided are tuned RF level measurements, level measurements, analogue modulation, and spectrum analysis. It can be equipped with powerful hardware for high-end phase noise test supplementary to the standard phase noise test with the spectrum analyzer. It also offers digital and analogue modulation signal analysis, 80MHz analysis bandwidth, analysis of pulses, and VOR/ILS signals. As a single-box instrument, it is designed to reduce the complexity in calibration capabilities for the A&D industry.

Rohde & Schwarz
www.rohde-schwarz.com



Linear DC power supplies

The DP813A and DP822A are two new models of high-performance linear DC power supply products that meet the market demand for low-ripple, high-current, linear power supplies. The DP813A is a single-channel, dual-range power supply providing 8V/20A or 20V/10A, while the DP822A is a dual-channel power supply



for 5V/16A or 20V/5A. The new models provide a programmable linear power supply with high current, low ripple, and high precision for many industries and applications such as optical communication module testing, chip and integrated circuit testing, semiconductor testing, and industrial ATE testing.

RIGOL Technologies
www.rigol.com

Interface camera industrial imaging

The Falcon4-CLHS M4480 camera, based on the Teledyne e2v Lince 11.2M monochrome sensor, delivers an easy-to-use CLHS interface camera that has been specifically engineered for industrial imaging applications

requiring high-speed data transfer such as machine vision industrial automation, flat panel display inspection, semiconductor inspection, PCB automated optical inspection, aerial imaging, and general machine vision applications. This latest model can reach a frame rate of up to 609fps in full 11.2MP resolution, and multiple thousands of frames per second in partial scan mode. When using the sensor's binning mode, it can reach a very large pixel capacity of over 160Ke.

Teledyne DALSA
www.teledynedalsa.com

Fixed acoustic imager

The SV600 fixed acoustic imager enables users to detect, locate, and visualise air and gas leaks or changes in sound signatures across their process and equipment in real time before they become costly problems. By using an array of sophisticated sound sensors and powerful SoundMap technology, it translates the sounds that it hears into a visual representation so you can quickly locate and quantify problem areas. The SV600 easily integrates with factory systems and can serve as an early warning system that can quickly detect changes across compressors,

