

**You don't know  
how much you  
don't know.**

# electronics

The image shows the cover of the October 2013 issue of Electronics magazine. The cover is tilted and features a large, stylized orange 'e' logo for 'electronics'. Above the logo, it says 'AI AND ROBOTICS SPECIAL' and 'OCTOBER 2013'. A white robot head is visible on the right side. A red banner with white text says 'FOR YOU'. The bottom left has the text 'ARTIFICIAL INTELLIGENCE' and 'What's Next?'. The bottom right has the text 'The 64 Q: Creating an AI Assistant' and 'Voice: Personalization Continues'. The top right corner has the price '\$100'.

OR This Code



Also available at all leading magazine outlets

## IR Remote Code

[illegible]

```
static const IrSequence irSequence0(array0, sizeof(array0) / sizeof(microseconds_t));
static const IrSequence irSequence1(array1, sizeof(array1) / sizeof(microseconds_t));
static const IrSequence irSequence2(array2, sizeof(array2) / sizeof(microseconds_t));
static const IrSequence irSequence3(array3, sizeof(array3) / sizeof(microseconds_t));
static const IrSequence irSequence4(array4, sizeof(array4) / sizeof(microseconds_t));
static const IrSequence irSequence5(array5, sizeof(array5) / sizeof(microseconds_t));

static const IrSequence irSequence6(array6, sizeof(array6) / sizeof(microseconds_t));
static const IrSequence irSequence7(array7, sizeof(array7) / sizeof(microseconds_t));
static const IrSequence irSequence8(array8, sizeof(array8) / sizeof(microseconds_t));
static const IrSequence irSequence9(array9, sizeof(array9) / sizeof(microseconds_t));

static const IrSequence irSequenceU(arrayU, sizeof(arrayU) / sizeof(microseconds_t));
static const IrSequence irSequenceD(arrayD, sizeof(arrayD) / sizeof(microseconds_t));

static const IrSequence irSequenceF(arrayF, sizeof(arrayF) / sizeof(microseconds_t));
static const IrSequence irSequenceB(arrayB, sizeof(arrayB) / sizeof(microseconds_t));
static const IrSequence irSequenceO(arrayO, sizeof(arrayO) / sizeof(microseconds_t));
```

```
static dutycycle_t dutyCycle;
IrSender* irSender;

void setup() {
    Serial.begin(115200);
    while (!Serial);
    if (Board::getInstance()->hasHardwarePwm())
        Serial.println(F("Hardware PWM available!"));
    else
        Serial.println(F("Hardware PWM NOT available, will be emulated in software."));
    randomSeed(analogRead(A0));
    dutyCycle = (dutycycle_t) random(20,80);
    irSender = IrSenderPwm::getInstance(true, PIN);
}
```

68 | DECEMBER 2021 • electronics FOR YOU ■■■