



Fig. 4: Author's single phase energy meter showing blinking LED

Construction and testing

An actual-size PCB for optical wattmeter is shown in Fig. 2 and its component layout in Fig. 3. After assembling



Fig. 5: Suggested enclosure for the optical wattmeter

the circuit on PCB, enclose it in a suitable plastic box.

Before mounting the Arduino on PCB, do not forget to upload the program on Arduino Nano board. Install photo-transistor L14F1 on the front

EFY Note

The source code of this project is available for free download at source.efymag.com

panel such that it can capture the blinking LED light from energy meter.

This circuit is developed for the energy meter having 6400 impulses/kWh. This can be changed in the program.

This circuit works on single phase supply only. Due to the low count of components, the circuit can be modified with a small OLED display and fitted into an enclosure like that of a non-contact thermometer (Fig. 5). **EFY**



A. Samiuddin, a circuit designer, is B.Tech in electrical and electronics engineering. His interests include LED lighting, power electronics, microcontrollers, and Arduino programming

Looking for Business Opportunity?

BECOME A DEALER FOR INDIA'S LEADING EDUCATIONAL KITS BRAND

A WIDE RANGE OF ELECTRONICS KITS AND TRAINING MATERIAL FOR ENGINEERING STUDENTS, ENGINEERS, HOBBYISTS, COLLEGE LABS & TRAINING INSTITUTES

Find Our Dealer Near You: kitsnspares.com/dealers

Interested? Call Shyam (8800100761)

To view our entire range of products, visit our website: www.kitsnspares.com

kitsnspares
For the 'engineer' in you

kitsNspares.com D-87/1, Okhla Industrial Area, Phase 1, New Delhi 110020
Phone: +91-11-26371661 • E-Mail: info@kitsnspares.com

SUPPLIERS INVITED
If you want to sell through our network