

MCUs add rich analogue features and up to 18 kilobytes of RAM, with competitively priced package options up to 48 pins. In addition, the STM32G0B0 Value Line, STM32G0B1 and STM32G0C1 MCUs introduce new features to the STM32G0 series by integrating a USB 2.0 device/host controller and dual-bank Flash memory.

STMicroelectronics
www.st.com

NAND solution

Micron Technology has begun volume shipments of 176-layer NAND universal Flash storage (UFS) 3.1 mobile solution. Engineered for high-end and flagship phones, Micron's discrete UFS 3.1 mobile NAND unlocks 5G's



potential with up to 75% faster sequential write and random read performance


than prior generations, enabling downloads of two-hour 4K movies in as little as 9.6 seconds. The 176-layer NAND offers a compact design ideal for the high-capacity, small form factors required in mobile devices. This launch brings high performance, design flexibility, and low power consumption to professional workstations and ultra-thin notebooks. Now available for smartphones, Micron's industry-pioneering advanced NAND technology and performance enables a more responsive mobile experience with true multitasking across apps.

Micron Technology
www.micron.com

Radiation-tolerant NOR Flash

Infineon Technologies has announced the industry's first high-density radiation-tolerant (RadTol) NOR Flash memory products qualified to MIL-

PRF-38535's QML-V flow (QML-V Equivalent). The QML-V flow is the highest quality and reliability standard



certification for aerospace-grade ICs. Infineon's 256Mb and 512Mb RadTol NOR Flash non-volatile memo-

ries deliver superior, low-pin count, single-chip solution for applications such as FPGA configuration, image storage, microcontroller data and boot code storage. The devices are radiation-tolerant up to 30krad (Si) biased and 125krad (Si) unbiased.

Infineon Technologies AG
www.infineon.com

Long-life button cells

VARTA's primary lithium coin cell CR1216 can be used to power small-size sensors due to its special assembly and low weight.



Because of its low internal resistance, a high pulse load can be supported. The

button cell has a runtime of up to 15 years and a low self-discharge for long storage and operating time. It can withstand a wide temperature range and has UL certification.

VARTA AG
www.varta-ag.com

AC-DC converter

The RAC05-K/PD3/H from RECOM is a board-mounted 5W Class II AC-DC converter series, intended for fixed installations where higher levels of transients according to



over-voltage category III are experienced, along with increased environ-

mental pollution levels. The converters are available with 5V, 12V, or 15V single outputs and include enhanced clearances to meet OVCIII up to 5000m altitude. Nominal input ratings are 100V AC to 277V AC, but the parts will withstand 480V AC continuously without damage. The series is rated for operation in 'Pollution Degree 3' environments, where pollution can become conductive if condensation occurs.

RECOM Power GmbH
www.recom-power.com

MODULES & BOARDS

AC-DC power supply

The TMW is a line of fully encapsulated AC-DC power supplies designed for medical, household, and industrial applications.




All models come in compact, dust resistant and waterproof IP68 housings.

These are IEC/EN 62368-1, IEC/EN 60335-1, and IEC/EN 60601-1 3rd edition compliant and are certified for 2xMOPP. Featuring a reinforced isolation, the power supplies are prepared for protection class II applications. Their wide operating temperature range of -20°C to +80°C makes them ideal candidates for demanding applications.

TRACO Power
www.tracopower.com

Development Board

Nuvoton Technology, a provider of microcontroller platform solutions,



announces Mbed OS 6 supported NuMicro M2354 series

IoT security MCU development board



WE LOVE TO SHOWCASE NEW PRODUCTS!

Launched a New Product related to electronics?
Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!