

for Armv8-M architecture. M2354 series supports the high-security requirement of IoT devices with outstandingly low power performance. The embedded 1MB Flash and 256kB SRAM memory facilitate multi-RTOS running on connected IoT devices, being easily massively deployed in the IoT environment targeted for high security, low power with a wide range of software resources supported.

Nuvoton Technology
www.nuvoton.com

Computer-on-module

congatec, a provider of embedded and edge computing technology introduces 20 new computer-on-modules following the launch of Intel's 11th generation Core processor for IoT. Featuring 11th Gen Intel Core vPro, Intel Xeon W-11000E, and Intel Celeron processors, the new modules target the most demanding IoT gateway and edge computing applications. Built on Intel's 10nm SuperFin technology in a two-package design with dedicated CPU and platform controller hub the new flagship COM-HPC Client and COM Express Type 6 modules impress with a new bandwidth benchmark of up to 20 PCIe Gen 4.0 lanes for massive connected real-time IIoT gateway and intelligent edge computing workloads.

congatec
www.congatec.com

Computer-on-module

ADLINK Technolog Inc. introduces its new Express-TL COM Express Type 6 module with Intel Core, Xeon W, and Celeron 6000 processors and octa-core (8-core) performance. Intel UHD Graphics and Intel AVX-512 VNNI provide superior artificial intelligence inferencing performance. The Express-TL is well-suited for image processing and analysis, high speed video encoding and streaming, medical ultrasound, predictive traffic analysis, and other demanding applications. With vibration resistance, wide

operating temperature range, and reliable system performance, the module helps shorten development cycles and reduce costs.

ADLINK Technology
www.adlinktech.com

Thermal camera

Teledyne's MicroCalibir is a compact, low-power camera platform. This latest uncooled thermal camera platform features the smallest VGA IR core module on the market, making it ideal for OEM drones, handhelds, helmet-mounted and vehicular integration products. It is equipped with 12µm microbolometer pixel technology with a deep-ADC ROIC circuit. This novel ROIC design results in a 1000°C intra-scene temperature range at a sub-50mK NETD. The MicroCalibir platform delivers accurate and high-end thermal capabilities and can be configured by resolution, field of view, and frame rate, to deliver optimal performance in applications such as UAVs, security and surveillance, outdoor recreation/personal vision systems, firefighting, and many more.

Teledyne DALSA
www.teledynedalsa.com

Power supplies

CUI has added twelve models to its VMS-C and VMS-C-CNF range of internal medical AC-DC power supplies. Considerably extending the offering, these new, higher power models are chassis-mount units available in open frame or metal case variations for use in medical and health-care applications such as ultrasound machines and medical beds. Featuring a universal input voltage up to 264V AC and output voltages of 12, 15, 24, 27, 36, and 48V, these power supplies can also be adjusted using an onboard trim pot. Offering safety and durability, the units can operate in a wide operating temperature range of -40 to +70°C (+85°C for the 100/120W products).

CUI
www.cui.com

Evaluation board

FTDI Chip has announced a new development solution based on its FT4233HP multi-channel interface ICs. The new FT4233HP high-speed USB serial/FIFO evaluation board will enable engineers to get started much quicker on implementing USB power delivery arrangements. This could be for the retrofitting of this functionality into legacy designs that are already in operation, or in relation to new items of equipment they are prototyping. The board size is 138.5mm x 77mm, with a pair of Type-C power delivery ports incorporated into it. The FT4233HP evaluation board will be available in Q4 2021.

FTDI Chip
www.ftdichip.com

T&M SOLUTIONS

Intelligent power supplies

Advanced Energy has expanded its presence in the test and measurement market with the launch of intelligent laboratory series iLS of programmable DC power supplies. With industry-leading small footprint and high power density, the iLS600, iLS600-R, and iLS1500 feature programmable capability with best-in-class measurement accuracy and a patented wireless remote sense feature that significantly reduces noise in a wide range of test and measurement applications. Designed for both benchtop and rackmount applications, the compact, lightweight units incorporate embedded 12-bit D/A and A/D converters for highly accurate voltage and current measurement.

Advanced Energy
www.advancedenergy.com

Distance sensor

Acuity Laser has released AS2100, a highly accurate laser distance

