


and reduce the rate of rejection, thus increasing both quality and productivity. By measuring the duration of switching operations with



extreme precision, the module is able to detect even the slightest deviations, which can point to component wear, changes in temperature, or other environmental factors. This enables automatic compensation for deviations from expected switching times and implementation of predictive maintenance strategies.

B&R Automation

www.br-automation.com

CHEMICALS & ADHESIVES

Adhesive solution

Indium Corporation has released NC-702, a no-clean, near-zero residue, halogen-free adhesive solution designed for holding parts in place during placement and reflow processes.



Designed for use in a formic acid reflow environment, it is specially formulated with high tack to hold a die, chip or solder preform in place without movement, creating a low-cost tooling-free solution over pick and place investments. While NC-702 has the tack strength to hold materials in place, the material is completely evaporated out during reflow, eliminating the time-consuming post-reflow residue cleaning steps.

Indium Corporation

www.indium.com

ENTERPRISE CLASS

IoT face detection system

Maxim Integrated's MAX78000 ultra-low power neural-network microcontroller

detects and localises faces in video and images using Xailient's proprietary Detectum neural network. Xailient's



neural network draws 250x lower power (at just 280 micro-Joules) than conventional embedded solutions, and at 12 milliseconds per inference, the network performs in real time and is faster than the most-efficient face-detection solution available for the edge.

Maxim Integrated

www.maximintegrated.com

Platform for biometric card

Infineon Technologies AG and IDEX Biometrics ASA have announced a



reference design for the next-generation biometric smart card architecture. The reference design

leverages the combination of Infineon's new SLC38BML800 security controller with additional GPIO interfaces and the latest generation of the TrustedBio solution from IDEX Biometrics. This enables fingerprint authentication with low latency, high accuracy, and power efficiency. The integration of the fingerprint sensor, the secure element, power management, and communications reduce the complexity of card manufacturing, which shortens time to market and lowers costs.

Infineon Technologies AG

www.infineon.com

Touch tablet

Avalue Technology has added a 17.8cm (7-inch) embedded multi-touch tablet OFT-07W33 to its best-selling open-frame OFT series, which allows for more flexibility and customisation in applica-

tions, and enables a wide range of usage scenarios. Building on its legacy of open frame architecture for easy installation



and maintenance, and highly flexible design, the OFT-07W33 is a boost to the existing range of applications with usage

Avalue Technology

www.avalue.com.tw

Multi-power UPS

Riello Power has expanded the family of modular multi-power UPS, designed



to protect data centres and critical applications, with the new 75kW combo cabinet (MPX 75 CBC). It can accommodate three modules of 15kW or 25kW (of the same power) and is ideal for IoT and edge computing applications, where the load is not excessively high, but space is at a premium.

Riello Power India

www.riello-ups.in

Indoor LoRaWAN gateway

The indoor LoRaWAN gateway known as NANOGTW-IDV has been launched by SSTPL.



It comes with a high-performance LoRa chipset. This made-in-India device is best suited for automatic meter readings, industrial applications, POC purpose, sensor integrations, home automation and security.

SSTPL

www.sstpl.in

THE COMPLETE MAGAZINE ON OPEN SOURCE

OpenSource
ForYou

The latest from the Open Source world is here.

OpenSourceForU.com

Join the community at facebook.com/opensourceforu

Follow us on Twitter @OpenSourceForU