



Fig. 6: View of plastic box housing for the prototype

board use SMD components. (During testing at EFY Lab, the LM358 based amplifier was first tried but it gave quite a low sound.)

Alternative possibilities

Instead of the clock, one can change the program to make it a seconds timer that could be used as a 100-metre race

timer, for instance. For this, pin 9 used for the buzzer can instead be used as input for the limit switch to stop it when the racer reaches the goal line. This pin should be set up by the code line 'input pull up.'

It is possible to show temperature also on the display in degrees Celsius. The analogue input pin A0 of Arduino



Fig. 7: PAM8403 audio board

can be wired to an LM35 temperature sensor. The 'analog reference' may be set up at internal 1.1V full-scale for maximum accuracy. The clock and temperature can be shown together. The program can be written to show the temperature for just five seconds at the beginning of every minute and then revert back to clock. **EFY**



Prof. K. Padmanabhan retired as a professor at A.C. Tech and University of Madras

Wanna Be Your Own Boss?

DO OPEN SOURCE.



www.opensourceforu.com

Demand for Open Source is sky rocketing. Be it for managing IT infrastructure or development of software—Open Source solutions are what customers are seeking.

All you need to do is develop expertise in an Open Source stack, and then build a team around it!

And, Open Source For You can be your friend and a guide through this journey.

TO READ OUR PRINT EDITION Visit: <https://subscribe.efyindia.com>

TO READ OUR EZINE EDITION Visit: <https://ezine.lfymag.com>

WORLD'S LEADING PUBLICATION ON OPEN SOURCE

Looking for marketing solutions to engage with cutting edge techies?
Contact us at growmybiz@efy.in OR call us at +91-9811155335.

