



Samwha Electric is with you! Samwha Electric Co. Ltd.

You will see that you are surrounded by countless electronic devices and infrastructure

Every electronic device needs a capacitor

Hybrid Cap (Conductive Polymer Hybrid Aluminum Electrolytic Capacitor)

Characteristics	Tantal capacitors		Aluminum Capacitors		
	Tantal	Polymer Tantal	Liquid Electrolyte	Polymer Al Cap	Hybrid Cap
Electrolyte	MnO ₂	Conductive Polymer	Electrolyte	Conductive Polymer	Liquid Electrolyte Conductive Polymer
Max. Voltage	Weak (50V)	Weak (35V)	Excellent (450V)	Weak (50V)	Excellent (100V)
ESR	Normal	Excellent	Weak	Excellent	Excellent
Dissipation		Excellent		Excellent	Excellent
Ripple current		Excellent		Excellent	Excellent
Reliability		Excellent		Excellent	Excellent
Leakage current	Weak	Weak	Excellent	Weak	Excellent
Failure Type	Weak (Short)	Weak (Short)	Excellent (Open)	Weak (Short)	Excellent (Open)

· Electrolyte consists of electrolyte and conductive polymer, and it enabling high voltage and miniaturization compared to solid electric capacitors

· **Application** : Automotive, Communication Home Electric Application LED, Medical, IT (PC, NOTEBOOK)



SAMWHA ELECTRIC

Samwha India Energy Savings Pvt. Ltd.

(Noida Office) C-35, Sec-2, Gautam Budh Nagar, Noida - 201301, (U.P.), India

(Bangalore Office) S-422, Manipal Centre, No-47, Dickenson Road, Bangalore, India.

Tel : +91-120-4571-339 E-mail : india_sales@samwha.com

Samwha Electric Co. Ltd.

3, Bongmyeong-ro, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, Korea (28589)

Tel : +82-2-2056-1646 FAX : +82-2-542-8554

<http://www.samwha.com/electric> E-mail : sesale1@samwha.com