

efficient way. With a fully integrated ultra-low impedance, high-voltage synchronous rectifier, and low drop-out linear regulator, the STWLC88 achieves high efficiency and low power dissipation, which is critical for applications that are highly sensitive to unnecessary heat buildup.

STMicroelectronics
www.st.com

Piezoelectric safety switches

To provide better safety in potentially explosive atmospheres such as refineries, mills, and chemical industries, the switches from SCHURTER PSE EX family feature aluminium or stainless-steel housings, offering maximum reliability and long service life. Due to their hermetically sealed housing (IP69K) with no mechanical switching contacts, these are designed for use in potentially explosive installations above ground, as well as in areas with flammable air-gas mixtures, vapours, and dust.

SCHURTER
www.schurter.com

Power management IC

The AEM10941 power management IC (PMIC) provides a robust energy harvesting solution. It covers a voltage range of 50mV to 5V input voltage and possesses an ultra-low power-up (from just a 3µW input). The IC is optimised for photo-voltaic-based energy harvesting deployments. It can acquire periodic data on the operational status of

non-powered assets situated in remote locations and then transmit them to the cloud. Any issues that could cause malfunction may then be identified and attended to. Key applications of these gateway modules are in diesel generators, fuel tanks, container units, and various other kinds of mobile industrial assets.

E-peas
www.e-peas.com

SENSORS

Solid-state LiDAR

The Velarray H800 is a solid-state sensor built using Micro-Lidar Array (MLA) architecture for superior automotive-grade performance. With combined



long-range perception and a broad field of view, this sensor facilitates safe navigation and collision avoidance in advanced driver assistance systems and autonomous mobility applications. A field of view of 120 horizontal degrees by 16 vertical degrees provides outstanding peripheral detection of near-field and overhead objects while addressing corner cases on sloping and curving roads. The sensor also supports perception data at a range of up to 200 metres, allowing safe stopping distances even at highway speeds.

Velodyne Lidar
www.velodynelidar.com

Flow sensor

With the new FLS110 flow sensor, flow measurement can now be incorporated into virtually any product or system. Its small size makes it perfect to be fitted into any product and be positioned where measurements matter. It measures a flow rate across a wide measurement range of 0.001 to over 500 standard litres per minute and delivers a fully temperature-compensated and reliable flow signal.

Flusso
www.flussoltd.com

Motion-tracking sensor

The IAM-20680HP is a high-performance automotive monolithic 6-axis motion-tracking sensor platform for automotive, telematics, and navigation system applications. It combines a 3-axis

gyroscope and a 3-axis accelerometer in a thin 3 × 3 × 0.75mm (16-pin LGA)



package. Additionally, the IAM-20680HP provides industry-leading sensitivity tolerance and temperature

stability in combination with proven high robustness by supporting 10,000g shock reliability. Other features include programmable digital filters, an embedded temperature sensor, programmable interrupts, I2C and SPI serial interfaces, and voltage operating range of 1.71V to 3.6V.

TDK Corporation
www.tdk.com

MODULES & BOARDS

Graphic TFT displays

The compact TFT displays from Electronic Assembly GmbH have brightness up to 1000cd/m², allowing clear readability in direct sunlight. Whether in the operating room or an outdoor measurement



station, a single glance at these displays is enough to obtain the required information. Thanks to their All Angle Colour Stability (AACs) technology, contrast and colours of these graphic displays remain unchanged even at extreme viewing angles. The displays come with a capacitive multi-touch surface, are compatible with any kind of microcontroller, and have been designed for tough, continuous industrial use.

Electronic Assembly GmbH
www.lcd-module.com

Cellular module

The AVT9152 module fulfills the demanding requirements of cellular connectivity yet consumes low power and has a minimal component size. It incorporates Nordic Semiconductor nRF9160

