


driver with an integrated charge pump. The MM101 driver provides a cost-effective solution for microelectromechanical system (MEMS) devices



and other high-voltage driving applications. The highly integrated voltage divider

provides up to eight drive outputs, programmable from 80 or 90V, in a miniature 5mm × 5mm 32-pin QFN or WLCSP flip-chip package powered with 5V charge pump and 3.3V driver circuit supply sources. It offers various protection features, including interface fault indicators, power-on-reset, power on/off sequence control, and under-voltage protection for charge pump and supply voltage. The MM101 driver provides a compact, power-efficient solution for driving the MEMS based switches, thus bringing size, weight, power, and cost benefits to a wide range of applications.

Menlo Micro

<https://menlomicro.com>

BOARDS AND MODULES

High-density AC-DC power supplies

The SL Power NGB800 800 W and NGB1200 1200 W from Advanced



Energy are AC-DC power supplies for medical and industrial power conversion platforms. The power supplies offer one of the highest

power densities in the industry and a high efficiency of up to 90%. The supplies come with medical and industrial safety and EMC approvals and are suitable for operating at a wide input range of 85 to 264V AC and provide output voltages from 12 to 48V DC. Both the power supplies are convection cooled, which makes them suitable for ventilated spaces, while the 1200W NGB1200 power supply also features a low-noise fan that makes

it more reliable for power-intensive applications. The power supplies are optimised for addressing performance and reliability in a small form factor, making them suitable for power-intensive systems capable of meeting high requirements of industrial and medical applications.

Advanced Energy

www.advancedenergy.com

Regulated DC/DC converters

RXM series is a family of surface-mount, cost-effective, regulated DC/DC converters from RECOM Power.

The RXM series includes R5M, R3M,



R2M, and R1M, rated at 5W, 3W, 2W, and 1W, respectively. All the modules feature a common case size

of 13.2mm × 9.1mm footprint, 10.2mm height, with the R2M additionally available in a through-hole DIP8 package. The RXM series operates over a 4:1 input range of 9-36V DC or optionally 18-75V DC, while the R3M, R2M, and R1M range additionally include 4.5-18V input. The modules offer an isolation rating of 1.6kV/1min.

The RXM series offers various safety features, including no minimum load operation, continuous short-circuit protection, and an on/off control pin. The DC/DC converters have an efficiency of up to 84% and come with an advanced circuit and thermal design results.

RECOM Power

www.recom-power.com

Network storage interface card

iWave's SmartNIC storage accelerator card is an FPGA based network interface card that



can enhance the server's compute capacity. The SmartNIC

can help offload the tasks from the host server's CPU and accelerate the workload. This can enhance the con-

nectivity and communication between a computer and a network, which can further increase the data and signal processing capability of the server.

The SmartNIC features dual front panel QSFP DD Cages-2x 200GbE/4x 100GbE Ethernet and high-performance storage extension with triple NVMe slots. The module also offers The 3/4 Length PCIe Gen3 x16 host interface on the board that connects the SmartNIC to the computer/server. This NIC card can help leverage the internet speeds offered by the service provider and offers multiple advantages, including better security functions that can protect the CPU from malicious attacks.

iWave

<https://www.iwavesystems.com>

SoM for ML edge devices

VAR-SOM-MX93 from Variscite is a system-on-module (SoM) for energy-efficient machine learning (ML) edge devices. The VAR-SOM-MX93 is designed to accelerate ML and offers



an energy-flex architecture for efficient processing. It

features a 1.7GHz Dual Cortex-A55 NXP iMX93 processor and an additional 250MHz Cortex-M33 real-time co-processor with a dedicated Neural Processing Unit (NPU) 0.5 TOPS and built-in security features. The SoM offers industrial features like 2x CAN bus, 2x GbE, and industrial temperature grade plus a wide range of features and connectivity options, such as camera inputs, audio in/out, ADC, 2x USB, certified dual-band Wi-Fi, BT/BLE, and display outputs. The VAR-SOM-MX93 is included in Variscite's long-term longevity plan and will provide an expected availability of 15 years. This SoM can enhance energy efficiency of the products and offer designers reduced development time, costs, and risks.

Variscite

<https://www.variscite.com>