


Amateur radio receiver module

MAVERICK-603 is the first commercially available RF device with an open source chip. It is an easy to use, amateur radio receiver powered by an ATmega 1608 microcontroller (MCU).



The module comes in a small size measuring


5cm × 4.4cm and has an operating frequency range of 1 to 100MHz and a minimum signal strength of -25dBm. The use of low noise amplifier (LNA) in the module gives the chip an ability to amplify very low-strength signals, thus reducing the need for any additional external hardware. Since the FT8 is a digital weak signal communication used primarily by amateurs, the radio operators need no amateur radio license to receive FT8. For data transfer the module uses SPI and UART data interface.

Radio Stack

<https://www.radiostack.com>

CoM for on-device AI

ADLINK Technology has released COM-HPC-cRLS based on the Intel 13th Gen Core processors. The Client Type COM-HPC Size C module is based on Intel's 13th Gen Core desktop processors. It combines power



efficiency with performance and fulfills various demanding AI, graphics, and mission critical

IoT applications. The ADLINK COM-HPC-cRLS offers up to 24 cores and 32 threads to deliver superior multi-thread and multitasking performance. It harnesses up to 128GB DDR5 SODIMM and two 2.5GbE LAN. The computer-on-module (CoM) is built for the instantaneous on-device AI applications. The COM-HPC-cRLS is suitable for applications including industrial automation, autonomous mobile robot, autonomous driving,

medical imaging, entertainment, and video broadcasting.

ADLINK Technology

<https://www.adlinktech.com>

TEST & MEASUREMENT

Performance vector tester

R&S PVT360A is a VSG/VSA single-box performance vector tester from Rohde & Schwarz. The tester is suitable for high-speed, high-throughput testing of all forms of 5G FR1 base stations and small cells as well as



for RF components characterisation or production. The PVT360A has an operational frequency range from 400MHz to 8GHz that covers all 5G FR1 requirements. The optional second generator and analyser support multiport component tests, true MIMO testing, or simply double the test capacity. The PVT 360A is capable of fulfilling the demanding requirements of the test environment such as minimum error vector magnitude (EVM) in test signals and high test throughput. The low EVM of the R&S PVT360A signal generator provides high precision test signals for minimal measurement uncertainty.

Rohde & Schwarz

<https://www.rohde-schwarz.com>

MISCELLANEOUS

Halogen-free solder paste

Indium Corporation's SiPaste C201HF is released for fine feature printing with a halogen-free, cleanable solder paste. The solder paste combines a non-wet open



(NWO) performance with excellent stencil print transfer efficiency that can satisfy a broad range of process requirements and boost SPI yields. Moreover, the SiPaste C201HF leaves behind a cleanable residue, which

can easily be removed with a commercially available semi-aqueous cleaning solution, or it can be used as a standard no-clean paste in processes where post-reflow cleaning is not applicable. It offers consistent and tight solder deposit spread across multiple prints along with excellent response-to-pause performance. It offers minimal voiding on tight-pitch components, ensuring joint strength on small components and an excellent reflow performance on components that exhibit high warpage.

Indium Corporation

<https://www.indium.com>

Software for safer autonomous vehicles

FusionEngine software from Point One Navigation is a high-performance ASIL-rated precise location solution for automotive applica-



tions. The software is compatible with ST's Teseo-APP (Teseo ASIL Precise Positioning) GNSS chipset. The combined solution

assures functional safety at ASIL-B, a critical requirement for Level 3 + ADAS systems. FusionEngine can be easily integrated into a variety of host processors that are used for enabling Level 3 + ADAS and autonomous driving systems. FusionEngine combines data from multiple sensors to assure the high accuracy, safety, and integrity required for higher levels of autonomous vehicles. Point One's FusionEngine enables developers to complete the Functional Safety Concept Phase for their host system software integration. This includes the definition of Safety Goals, Functional Safety Requirements (FSR), and Technical Safety Requirements (TSR) as well as the test methods to provide evidence of successful integration.

Point One Navigation

<https://pointonenav.com>