

Prodigy PCIe Gen3/4 Protocol Analyzer

Prodigy Technovations Pvt. Ltd, a Bangalore-based company, introduces its PGY-PCleGen3/4-PA PCIe Protocol Analyzer supporting 2.5, 5.0, 8.0 and 16GT/S speeds. PCIeGen3/4 Protocol Analyzer is used for development and validation of PCIe interface for M.2, U.2 and Embedded PCIe Bus. Engineers in mobile, automotive and 5G network use this product to debug the protocol layer design problems in PCIe. PGY-PCleGen3/4-PA provides industry best solution to simultaneously monitor and decode PCIe traffic at 2.5GT/S to 16GT/s and supports protocol decode and analysis of TS1, TS2, DLLP and TLP packets. Detailed LTSSM view is provided to help the designers to see PCIe state machine transitions.



PGY-PCleGen3/4-PA Software does industry best decode and analysis of deep memory PCIe traffic saving debug time. Designers can quickly select and view the parameter of interest in the TS1, TS2, DLLP or TLP packet. Separate decode and analysis view of configuration packets exchanged between root complex and end point. Current generation Software GUI with multiple floating windows and flexibility to view the required packet content makes it easy to debug the design issues with flexibility to hide and unhide the columns. LTSSM Analysis in software provides graphical representation of different states of protocol layer along with substate information.

PGY-PCleGen3/4-PA Protocol Analyzer provides 64GB memory depth to capture the x4 link traffic. PCIe Protocol Analyzer supports trigger on content of the protocol packets and if-then-elseif multi-level trigger capability. This enables engineers to capture protocol details around the trigger condition and monitor PCIe bus over a long period of time.

Key Features:

- Simultaneous Protocol analysis of 2.5, 5, 8, and 16GT/S Protocol Traffic
- Acquisition memory management to capture protocol traffic using trigger, segmented memory, circular buffer and hardware filters
- Responsive software to analyze long captures with LTSSM view
- Active M.2, U.2 interposers and Solder down and custom probing Solutions
- Simple and advanced Trigger based on TS1, TS2, DLLP and TLP Protocol packet content

Prodigy UFS4.0 Protocol Analyzer



Prodigy Technovations Pvt. Ltd, provides PGY-UFS4.0-PA M-PHYSM, UniPro®, UFS4.0 Protocol Analyzer for development and validation of next generation flash memory UFS 4.0 at 23.2 Gbps per lane interface for 5G, Mobile, Automotive, IOT, AR/VR applications. PGY-UFS4.0-PA is the leading instrument that enables the design and test engineers to test the UniPro and UFS3.0 designs for its specifications. PGY-UFS4.0-PA is backward compatible with UFS2.0/2.1/3.0 and 3.1 specifications.

Deep Capture, Powerful Trigger capabilities and In-depth Analysis views give unprecedented insight into Universal Flash Storage 4.0, UniPro® and M-PHYSM Protocol layers. Multilayer View in PGY-UFS4.0-PA, provides the complete view of M-PHYSM, UniPro® and UFS Protocol activity in a single GUI. User can easily correlate protocol activities between protocol layers for quick debugging and finding the cause for protocol errors. User can set different trigger conditions to capture specific protocol activity and decode the communication between UFS4.0 Host and Device. Decoded data is displayed in symbol, UniPro and UFS layer packets. Error report provides the summary of different types of protocol errors in millions of protocol packets.

Key Features of PGY-UFS4.0-PA M-PHYSM, UniPro® and UFS4.0 Protocol Analyzer:

- Flexibility to capture very large data using continuous streaming of Protocol data
- Soldered-down active probe and custom designed probes provide high signal fidelity
- Real Time Protocol decode with error analysis
- Trigger based on MPHY, UniPro, UFS layer packet content
- MPHY, UniPro and UFS layer Protocol Decode
- Powerful search and Filter capability



For more info contact us:
Email: contact@prodigytechno.com
Web: www.prodigytechno.com