



NEW PRODUCTS

MAKE IN INDIA

COMPONENTS

Intelligent valve controller

Valmet Neles NDX 2.0 is an intelligent valve controller for valve automation in industries and plants. The next-generation valve controller features



renewed interface, making it simpler to use with all types of valves available in the market. The

pneumatic relay in the controller consumes up to 90% lower air compared to other conventional controllers, thus reducing energy consumption. The NDX 2.0 provides interoperability with the most common automation systems and is suitable for most operating environments.

Valmet

<https://www.valmet.com>

Radiation-tolerant PWM controller

The TPS7H5005-SEP is a radiation-tolerant, current mode, dual output PWM controller optimised for silicon and gallium nitride (GaN) based DC-DC converters in space applications. The switching frequency of the TPS7H5005-SEP can be configured from 100kHz to 2MHz while still maintaining a very low current consumption, which makes it ideal for fully exploiting the area reduction and high efficiency benefits of GaN based DC-DC converters. The device features integrated synchronous rectifier control outputs and dead-time programmability in order to target high efficiency and high performance topologies. The PWM controller is suitable for use in space satellite point of load supply for FPGAs, microcon-


trollers, data converters, and ASICs.

Texas Instruments

<https://www.ti.com>

Ultra-compact tactile switch

The TS19 series from CUI Devices is the industry's smallest tactile switch housed in a compact 3mm × 2mm × 0.6mm package. The series features an



IP67 rating which makes it suitable for use in locations with high humidity and environmental


contaminants. Moreover, the tactile switches are highly reliable and come with a lifecycle rating of up to 300,000 cycles. These tactile switch models feature surface mount packages, gull-wing terminations, SPST circuit types, and operating force ratings of up to 240 ± 50gf. The TS19 series are reflow solder compatible and suitable for 12V operation and can work at a temperature range from -30 to 85°C.

CUI Devices

www.cuidevices.com

Pulse withstanding chip resistor

RCPA is a series of automotive-grade pulse-withstanding chip resistors from Stackpole. The RCPA has limited to



no calibration trim, providing reliable and repeatable pulse handling behaviour. These resistors

are highly reliable and are AEC-Q200 qualified, which makes them suitable for use in harsh automotive conditions. The resistors are suitable for use in applications

which require high durability and long-term reliability, such as motor controls, thermostats, and oven controls, etc.

Stackpole

<https://www.stackpole.com>

6-axis IMU

LSM6DSV16X from STMicroelectronics is a 6-axis inertial measurement unit (IMU) that can precisely detect movement in a 3D space. It combines arti-



ficial intelligence, adaptive-self-configuration, and ST's sensor fusion low power technology for high power


optimisation. The IMU is capable of providing a fast, real-time response as all the processing is done in the MEMS sensor itself. The LSM6DSV16X also features a triple sensing core to meet the differing needs of user-interface controls and optical/electronic image stabilisation. The LSM6DSV16X is ideal for applications such as advanced 3D phone mapping, precise gesture recognition for XR headsets, always-on activity tracking, etc.

STMicroelectronics

<https://www.st.com>

Long range iToF imager

Infineon's novel pixel technology boosts 3D camera performance while lowering power consumption. The



IRS2975C is the industry's first sensor to utilise Infineon's pixel technology and works on the principle of indirect ToF (i-ToF) to detect

depth. The sensor comes in a small size and is suitable for various iToF applications. It is capable of delivering a very high possible operating range