


High-speed SerDes silicon

VS775 from VSI is the first commercial serialiser/deserialiser (SerDes) IC that complies with the ASA Motion Link standard. The VS775 provides a data transmission rate of up to 16Gbps



so that the ECU can quickly process high-resolution image data collected by vehicle image

sensors, especially electric vehicles and autonomous vehicles. The SerDes IC provides a commercial camera link semiconductor solution that will resolve the bandwidth concerns associated with using more high-resolution image sensors in advanced autonomous vehicle designs. The VS775 is a power-efficient IC in an ultra-compact size that can help designers build safer autonomous vehicles.

VSI

<http://www.vsitech.co.kr>

Module for V2X communication

Murata along with Autotalks have released Type 2AN, a wireless module that supports both the dedicated short-range communications (DSRC) and cellular V2X (C-V2X) standards of



V2X wireless communication. The Type 2AN module is a highly robust

module that can be employed in the most challenging of operating conditions. It is powered by a dual-core ARM Cortex A7 CPU capable of running V2X middleware and applications and an optional secure CAN microcontroller. The module comes in a compact size measuring just 38.5mm × 37.5mm × 8.5mm. It can be used in advanced applications such as early detection of unseen vehicles, traffic prioritisation and speed control, accident response, updates on road conditions, etc.

Murata

<http://www.murata.com>

T&M INSTRUMENTS

Radome and bumper tester

R&S QAR50-R is a fully automated turnkey solution for automotive radome and bumper testing based on the R&S QAR50.



It offers high flexibility and is capable of accurately testing in the automotive radar frequency range at the end-


of-line. The QAR50-R is a lightweight and flexible radome and bumper tester that offers higher throughput and yield than other devices. The new model combines the imaging capabilities of the R&S QAR and R&S QAR50 that allow for reliable and precise testing of large areas of the bumper. It is designed with a focus on compactness and low weight in order to be compatible with standard 6-axis robots. Due to its design, the R&S QAR50-R reaches positions that could hardly be handled with other available test systems.

R&S

<https://www.rohde-schwarz.com>

Conformal coating tester

CC-100 from Insituware LLC is a conformal coating thickness tester. It can measure the thickness of both wet and dry conformal coatings directly on production boards in less than 5 seconds. The



thickness tester uses a chromatic confocal measuring principle to determine the thickness of transparent layers. The non-destructive and contactless testing method is fast and provides accurate results to help electronics manufacturers meet requirements for quality standards.

Insituware

<https://www.insituware.com>

MISCELLANEOUS

Solder paste for LEDs

Indium Corporation's NC38HF is a new solder paste suitable for advanced LED soldering applications. The paste offers consistent and tight



solder deposits across multiple prints, enabling a better coverage

of soldering paste and higher quality prints. This new formula also provides minimal voiding on tight pitch that allows for stronger joints even for small components. It is a halogen-free and no-clean solder paste which leaves no traces after the soldering process. The solder paste is suitable for mini/micro LEDs of COB, COG, SMT, and other LED varieties.

Indium Corporation

<https://www.indium.com>

Smart soldering system

The smart SELECT Synchro selective soldering system from Nordson Electronics is suitable for high-volume printed circuit board (PCB) assembly applications. The soldering system offers better cost-of-ownership and provides flexibility for electronics



manufacturers. It can also improve throughput by 20-40% by employing a unique synchronous motion. Nozzles of different sizes and various solder pots are available to provide flexibility with solder quantities, solder alloys, and board designs. The smart soldering system comes in two models with the larger Synchro XL model capable of soldering boards up to 680mm × 2500mm in dimensions. The SELECT Synchro offers better yield and saves space for many through-hole and SMT boards.

Nordson Electronics

<http://www.nordson.com/electronics>