

ONBOARD IIoT DEVICES Seamlessly With The FDO Standard

Manual onboarding of a large number of Industrial Internet of Things devices into a network is cumbersome and comes with security risks. The FIDO Device Onboard (FDO) standard automates the process, making it simpler and safer

ANISHA GHOSH is an open source enthusiast and a contributor to open source communities and repositories. She is interested in various development based projects

ADITYA MITRA is a cybersecurity researcher. He likes to learn about the vulnerabilities of various kinds of networks. His areas of interest are IoT, networking, and cybersecurity

IoT or the Internet of Things has taken the world by storm. IoT devices may include devices ranging from smart speakers, smart TVs, and even doorbells, to Industrial IoT (IIoT) devices like construction vehicles, supply chain robots, and so on.

The International Data Corporation (IDC) expects the IoT market to surpass the US\$1 trillion mark in 2022. Industrial IoT is a major component of all IoT devices, and comprises the following.

Industrial things. This contains devices like robots, PLCs (programmable logic controllers), sensors, actuators, and so on. They are generally connected to microcontrollers and microprocessors for functioning.

Connectivity. As the name suggests, this is essential for providing internet or network connectivity to industrial things. It may contain switches, access points, routers, VPNs, gateways, and so on. These are responsible for creating and maintaining a network of industrial devices and connecting them to servers. Not all industrial things support Wi-Fi (IEEE 802.11) or internet connectivity. For such devices, other communication protocols like Bluetooth (RL78/G1D), Zigbee (IEEE 802.15), and LoRa WAN (IEEE 1451.0) are used.

Servers. This is where the main computing, storage, and operations happen, leading to the proper functioning of the cluster or group of industrial things. Depending on the industry, the server may be hosted on a cloud platform like AWS, GCP, or Azure or on on-premises machines. It is also possible that the

servers are on an offsite data centre.

Insights and actions. The administrator dashboards monitor the functioning, state, and condition of the industrial things. This allows them to take action on one or multiple devices from a remote computer or mobile device. This also provides event based alarms and alerts to the administrator in case of any issues or malfunctions.

So, Industrial IoT or IIoT needs an extensive setup and onboarding procedures—connecting through the network, enrolling on the servers, adding them to the analytics dashboard, and so on. The question then is: How long would it take to manually onboard a large number, for example, 10,000 gateways, devices, and sensors? According to a 2017 study by Kaiser Associates Research and Analysis, it would take over two man-years. Yes, it is pretty cumbersome work to onboard everything manually.

Hence, the FIDO Alliance has come up with an automated and secure IoT device onboarding standard, called FIDO Device Onboard, or FDO. It is a specification for automated and secure IoT provisioning.

The FIDO Alliance, which has been working on securing services and accounts in a passwordless way, came up with the FDO specification in 2020. After some minor modifications, the FDO Specification 1.1 was proposed in 2021.

The FDO standard is currently used in various IIoT devices, mainly devices based on Intel Arm. It has proved to be one of the essential standards in the fast, secure, seamless onboarding of IoT devices. It uses cryptographic technologies to verify the ownership of an IoT device and then enrolls

