

designed the processor to level up the entry gaming smartphones. It offers global dual 4G connectivity with intelligent connectivity technologies that will improve the network coverage of the smartphone.

MediaTek

<https://www.mediatek.com>

DIN rail terminal blocks

CUI Devices has released the TBDR family of terminal blocks to its existing line of DIN rail terminal blocks. The



TBDR family offers push-in spring or end-cap connector types with feed through or ground type

styles. These DIN rail terminal blocks are available in single-level or dual-level packages with 2, 3, or 4 position options, making them suitable for a range of DIN rail mount applications. The TBDR models accept wire sizes of 1.5 or 2.5sqmm, or gauges from 26AWG to 12 AWG, and come in black or gray colours. These terminal blocks carry UL current ratings of 15 or 20A and IEC current ratings from 16 to 24A as well as UL voltage ratings of 300 or 600V DC and IEC voltage ratings of 500 or 800V DC. All models support operating temperature ranges from -40 to 105°C.

CUI Devices

<https://www.cuidevices.com>

BOARDS AND MODULES

Workstation motherboards

ASUS has released a couple of Intel W790 workstation motherboards—the Pro WS W790E-SAGE SE and the Pro WS W790-ACE.



Both the motherboards are built for the latest Intel Xeon W-3400 and

W-2400 processors and are capable of handling full overclocking capability of the new processors. The Pro WS W790 series offers comprehensive hardware


and software-level remote management to keep IT on track. The Pro WS W790E-SAGE SE uses a dedicated gigabit Ethernet controller assigned to the onboard AST2600 BMC for the connection of IPMI architecture, allowing for BIOS updates, hardware resets, or critical issue fixes via a web UI. Both the motherboards are suitable to meet the high demand of graphic designers, data scientists, architects, engineers, etc and can also be used for application in complex designs, simulations, rendering, and AI inferencing workloads.

ASUS

<https://www.asus.com>

pH sensor module

Rajguru Electronics has released the ADIY pH sensor module, a sensor for measuring the potential of hydrogen (pH) in any liquid. The low-cost sensor can precisely measure the



hydrogen-ion activity in water based solutions. It offers better

accuracy than pH indicator solutions and litmus tests. The sensor can easily be integrated with Raspberry Pi and Arduino. It has a measuring range from 0-14pH and offers a resolution of $\pm 0.15\text{pH}$ at standard temperature and pressure. The module utilises hydrogen-ion activity, also known as the “proton activity” for measuring pH of the liquid. This kit’s drive board works with 9V systems, making it compatible with many MCUs, including the Arduino and Raspberry Pi. The pH sensor can be used in a variety of pH measurements with fast response and excellent thermal stability. It has good reproducibility and can eliminate basic alkali errors. In the 0pH to 14pH range, the output voltage is linear. The ADIY pH sensor module is suitable for use in applications where acidity and alkalinity testing is required.

Rajguru Electronics

www.rajguruelectronics.com

High-density DC-DC module

The PKB5213D from Flex Power Modules is a new introduction to company’s existing PKB-D series of isolated eighth-brick DC-DC converters. The PKB5213D is a high-density DC-DC converter suitable for harsh



environments. The power

module works with a wide

input voltage from 18-60V and provides a fully regulated 12V output delivering power up to 240W. The PKB5213D has high efficiency and can work at high temperatures. The isolated converter module saves the output loads from any fault occurring at the input side, making it suitable for sensitive appliances and use in automotive, medical, and industrial applications. The PKB5213D has high efficiency and can work at high temperatures.

Flex Power Modules

<https://flexpowermodules.com>

Programmable power supply

Advanced Energy has released an UltraVolt AEQ series of power supply that is suitable for a wide range of medical, life science, industrial, and



semiconductor equipment applications.

The power supply can deliver up to 600V DC at 0.5W output power from an input voltage of +5V DC.

The programmable supply offers a stable output voltage and enhanced isolation support and is suitable for critical high-voltage applications in medical and industrial sectors. A programmable power supply can be adjusted to provide a specific voltage and current output. The output can be programmed and controlled through software or other digital means, allowing for precise control and automation of the power supply in various applications. This type of power supply is commonly used in electronic test and