

measurements, research and development, and manufacturing processes. The precise and stable output voltage, small size and enhanced isolation of the UltraVolt AEQ series makes it suitable for use in high-voltage needs for medical, life science, industrial, and semiconductor applications.

Advanced Energy
<https://www.advancedenergy.com>

TEST & MEASUREMENT

Handheld spectrum analyser

Field Master MS2070A from Anritsu Company is a rugged battery-powered handheld spectrum analyser. It conducts reliable and accurate RF measurements



in a variety of general-purpose field, lab, and manufacturing environments. It has

a dynamic range of > 105dB at 2.4GHz, typical DANL with a built-in optional preamplifier of -167dBm, coupled with a Third Order Intercept of +11dBm and typical level accuracy of ± 0.5 dB, which enable a full range of signals to be analysed by the spectrum analyser. The MS2070A is designed for standard swept spectrum analysis up to 3GHz. It features sweep speeds of up to 32GHz/s in common low noise configurations. A number of "smart" measurements, including occupied bandwidth, channel power, and adjacent channel power are standard in the Field Master MS2070A. As many as six traces can be set simultaneously with different detectors. For long-term spectrum monitoring applications, the MS2070A has upper/lower, envelope, and alarm limits standard. The spectrum analyser is suitable for use in harsh environment.

Anritsu
<https://www.anritsu.com/en-IN>

EMBEDDED

Energy harvesting sensor

SMK's Gen 2 SCPS is a Bluetooth based ambient sensor with energy

harvesting capabilities. The Gen 2 SCPS sensor can collect ambient information, such as temperature, humidity, luminance, CO₂, air pressure, accelerometer, and ambient sound. Its harvesting capability can allow for a



• battery-free operation of low-powered electronics.

The energy harvesting capability and multi-sensing capability in a single package will enable the engineers to develop a lightweight, compact, and no-maintenance sensor node or other IoT devices that can communicate using Bluetooth. Energy harvesting sensors have the advantage of being self-sufficient and not requiring an external power source. This eliminates the need for batteries or external power supplies, which can save cost and maintenance, as well as increase the reliability and lifespan of the sensor. Additionally, energy harvesting sensors can be used in remote or inaccessible locations where power sources are not available.

SMK
<https://www.smkusa.com>

Universal housing for PCBs/SBCs

Phoenix's UCS series of housings offer an adjustable and universal solution to accommodate PCBs or single-board computers (SBCs). The IP40 housings can reliably protect PCBs in a standard form factor and custom-designed



PCBs from external influences. They can reduce

the required space and can be easily mounted on DIN rail or wall. Moreover, the housings can also be used as a desktop with the help of few accessories, thus offering flexibility in the mounting style. The company offers various versions, including one with a flexible PCB attachment, or with a fixed PCB attachment that is integrated into the corner dome. The removable side panels enable a

modular electronic solution, which can be cut according to the requirement of the connection technology to be used. There is a stronger version made out of aluminium for higher strength, suitable for harsh industrial environments.

Phoenix Contact
<https://www.phoenixcontact.com>

Low-power embedded system

Variscite has released the VAR-SOM-AM62, a module for low-power embedded systems. The SoM is powered by the Texas Instruments AM62x, a low-cost MPU with scalable



Arm Cortex-A53 performance and embedded features. The

VAR-SOM-AM62 runs on 1.4GHz Quad-core Cortex-A53 with 400MHz Cortex-M4F and additional 333MHz PRU real-time co-processors. It offers camera interface MIPI-CSI2, integrated 3D GPU along with dual LVDS display. The VAR-SOM-AM62 is a low-cost device starting from only \$33, making it suitable for low-cost embedded industrial products that require high performance and low power. The SoM offers multiple connectivity features, including a certified dual-band Wi-Fi, BT/BLE 5.2, 3x CAN bus, dual USB, and dual GbE. Moreover, it supports industrial operating temperatures. The SoM is a member of Variscite's Pin2Pin product family, allowing developers to use the same carrier board design for a wide range of processors.

Variscite
<https://www.variscite.com>

MISCELLANEOUS

DSP IP for in-car entertainment

Cadence Design Systems has released a digital signal processor (DSP) IP in Cadence Tensilica HiFi DSP IP. It is the first DSP IP supporting Dolby Atmos for car. The Dolby Atmos can enhance the immersive sound experi-