

ence for in-car entertainment systems while reducing energy consumption. The Dolby Atmos can also provide the sound signature and playback



quality as intended by the music artist. It offers greater audio details, clarity,


and sound separation, thus improving the overall music experience. The Tensilica processor cores can be integrated into SoC designs to provide specialised processing capabilities. The software development tools include compilers, debuggers, and others that enable developers to efficiently create and optimise software for the Tensilica cores.

Cadence

<https://www.cadence.com>

3D printer with air manager

The UltiMaker S7 is a new and advanced 3D printer from Ultimaker. It is an upgrade over the company's best-selling series of 'S' 3D printers. It features a new flexible build plate that



makes removing the printed parts easier. Moreover, it comes with an integrated air manager that filters out up to 95% of ultrafine particles and improves temperature regulation, thus

enhancing the quality of printed parts. The S7 also features an improved automated bed levelling that improves the first-layer adhesion, making it possible to print bigger designs with a smaller base. Advances in temperature regulation on the S7 allow users to capitalize on the large 330mm × 240mm × 300mm build volume—with reliable accuracy from the first printed layer to the last. The flexplate also provides easy part removal post-printing, reducing labour, so users can get on with other tasks. The Ultimaker S7 Pro can hold up to 6 different spools

of filaments, enabling it to print multi-colour objects.

UltiMaker

<https://ultimaker.com>

Cavity pump for adhesives

LiquidFlow 2 from Meter Mix is a cavity pump system for extremely fine dispensing of adhesives and potting compounds. It can be configured



for either manual or robotic applications with a wide range of viscosities. The cavity pump can dispense very small and precise amounts of potting

compounds, which can reduce waste and improve the efficiency of the application process. Unlike many other cavity pumps, the LiquidFlow2 operates without pulsation, which enables it to apply very small beads and shots continuously and precisely. The compact metering and mixing system are configured for either manual or robotic application of two-component polyurethane, epoxy resin, silicone, and methacrylate. The LiquidFlow 2 is configured with twin progressive cavity pumps, which can be manufactured from different materials. It offers a high level of flexibility and allows user to store up to 50 different mixing ratios, flow rates, and shot quantities that can be stored via a recipe function. It also features an in-built anti-gel purge timer that prevents the material on the tip from curing in the disposable mixer nozzle.

Meter Mix Systems

<https://www.meter-mix.com>

MCU edge-AI developer cloud

STMicroelectronics has unveiled the world's first MCU edge-AI developer cloud. The STM32Cube.AI developer cloud opens access to an extensive suite of online development tools built around the STM32 family of MCUs. The STM32Cube.AI desktop front-end includes the resources for developers to validate and generate optimised

STM32 AI libraries from trained neural networks. This online tool offers interface to generate optimised C-code for STM32 microcontrollers, without requiring prior software installation. This new tool brings the possibility to



remotely benchmark models on STM32

hardware through the cloud to save on workload and cost. The tool can be used for various use cases, including human motion sensing for activity recognition and tracking, computer vision for image classification or object detection, audio event detection for audio classification, etc.

STMicroelectronics

<https://www.st.com>

Operating system for smart card

Infineon Technologies and TrustSEC have jointly developed BIO-SLCOS, an advanced operating system (OS) for smart cards. The OS employs Infineon's new high-performance SLC38 Secure Element to provide a



secured and open platform that integrates security, flexibility, and hardware

independence to achieve ease of use, performance, and security requirements of the global smart card market. The BIO-SLCOS can support contact, contactless, dual, and USB interfaces. Moreover, it can be preloaded or programmed with fixed applications or enable application uploading after using the card manager module. The solution is suitable for use in government identification, payment, ticketing, and access applications, as well as for application providers looking to enhance their biometric solution in terms of security, performance, and functionality.

Infineon Technologies

<https://www.infineon.com>