

receiver, and antenna functionalities into one chip, simplifying the complexities traditionally associated with such systems. It is designed precisely for high accuracy use cases, especially in auto tech and industrial applications. The resolution and bandwidth benefits of 240GHz radar are also applicable to industrial sensing applications, including material thickness measurement and analysis. The cascaded radar front end has an operating bandwidth of up to 45GHz at 240GHz. These unique features enable extremely high resolution, ideal for license-free 244 – 246GHz ISM band applications and beyond.

Indie Semiconductor
<https://indiesemi.com>

Multi-directional spring contacts for compact electronics

Harwin has launched a multi-directional spring contact range with height options ranging from 4.00mm to 10.00mm. The compact S1921-46R and S1931-46R have free heights of 4.00mm and 5.50mm, respectively,




while the taller S1981-46R is 8.50mm and S1991-46R is 10.00mm. Multi-

directional capability is needed for compact electronic layouts. It provides engineers with greater flexibility in connecting PCBs. The spring contacts can extend up to a free height of 10.00mm, and when factoring in their position over a PCB, they maintain a working height of 9.50mm. Current ratings of up to 14 amps enable the spring contacts to be used in low-level power delivery applications, signal transfer, and enclosure grounding tasks. They are typically used in communications equipment, consumer electronics, industrial control and monitoring systems, instrumentation, retail tracking devices, and kiosks.

Harwin
<https://www.harwin.com>

Voltage regulator module for AI applications

Flex Power Modules has launched the BMR511, a two-phase power stage for voltage regulator module (VRM) solutions. The module can be acquired with land grid array (LGA) or solder-



bump connections and is designed for bottom-side cooling. The design is specifically tailored for AI applications. It is uti-

lised by hardware components, including central processing units (CPUs), graphics processing units (GPUs), image processing units (IPUs), and high-performance application-specific integrated circuits (ASICs). The module functions within a 5-15 volts input and offers a flexible 0.5–1.8 volts output, controlled by an external mechanism using tri-state pulse width modulation (PWM) inputs. It can sustain a continuous current of 80 amperes and peak at 140 amperes, boasting a high efficiency of up to 94.5%. The VRM works between -40°C and 125°C. The module offers detailed thermal derating information for airflow speeds and cold plate/board temperatures. The voltage regulator module also incorporates fault reporting and over-current protection.

Flex Power Modules
<https://flexpowermodules.com>

High-power capable fuse holder

SCHURTER has launched the FXP shock-safe fuse holder specifically designed for high-power applications.



The fuse holder can accommodate 6.3 × 32 fuse-links and is engineered to handle rated currents of up to 25A (IEC) or 45A (UL). The component is well-suited for various applications, including equipment using a three-phase 400V AC supply and applications needing currents up to

25A as per the VDE (verband der elektrotechnik) standard. The fuse holder stands out for its high current capacity even at higher temperatures. While IEC and UL ratings are for around +23°C (IEC) or +25°C (UL), this fuse holder offers 4 watts at 50°C. Most similar-sized holders reach this only at room temperature, giving FXP an advantage in hotter conditions. Its ingress protection 40 (IP40) class makes it ideal for indoor applications. The fuse holder is designed for 600V AC applications and offers high-rated power acceptance. It stands out for its power-to-size ratio, robustness, and being the first to meet the extended IEC standard.

SCHURTER
<https://www.schurter.com/en>

Point-to-point antennas for next-generation connectivity

RadioWaves has launched a range of 6GHz antennas for the latest Wi-Fi 6e and upcoming Wi-Fi 7 bands. The antennas are suitable for multiple input multiple output (MIMO) applications. Available in type-N female and reverse polarity sub miniature version A (RP-SMA) male connectors, the antennas



are optimised for multiple-input, multiple-output (MIMO) uses. The collection features parabolic antennas with fre-

quencies ranging between 4.9GHz and 7.125GHz, granting users access to both the latest Wi-Fi 6e and the anticipated Wi-Fi 7 spectrum. Designed with dual slant and vertical/horizontal (V/H) polarisation, these antennas are easily adjustable. The antennas provide customers access to the newest 6GHz bands, covering Wi-Fi 6e and Wi-Fi 7. This ensures networks can manage multiple devices concurrently without sacrificing performance. Through the integration of the point-to-point antennas, networks can realise enhanced channel bandwidth, augmented access point (AP) capacity, and improved