

to the oscilloscope screen, achieving a precision 16 times nearer to perfection. The oscilloscope supports over 30 probes in nine categories, enhancing versatility. The MAUI with OneTouch interface offers intuitive operation, drastically reducing setup time with drag-and-drop. Most tasks can be done with a single touch, highlighting its user-centric design.

Teledyne LeCroy

<https://www.teledynelecroy.com>

## ENTERPRISE SOLUTION

### Private 5G solutions for enterprises

VVDN Technologies has introduced a dependable, secure, and ready-to-deploy 5G Enterprise solution. The private 5G package includes open radio access network (ORAN) radio units, customised central unit/distributed unit (CU/DU), and 5G Core. Driven by open, standard-based ORAN



architectures, the solution caters to ultra reliable low latency communications (URLLC) and enhanced Mobile Broadband (eMMB) needs, ensuring uninterrupted indoor coverage in dense environments. The cloud-native 5G core offers a dependable, scalable, and distributed network, aiding operators and integrators in deploying IoT, private networks, and multi-access edge computing (MEC) networks. The production-ready radio units are tailored for private 5G networks across diverse regions and markets. Their portfolio includes low power (4T4R 1W) and mid power (4T4R 20W) radio units optimal for private 5G setups.

VVDN Technologies

<https://www.vvdntech.com>

### Smoke and gas detectors for safety

Hikvision India has launched HF-S2E Eco and NP-FY200 in the photoelec-

tric smoke detector category and HF-GM100 in the carbon monoxide gas detector category. The photoelectric smoke detector is a smarter and faster solution for detecting smouldering fires than other smoke detectors. The detectors are designed to promptly detect smoke,



fire, and other hazards, triggering alarm signals to alert users. The carbon monoxide gas detectors find applications in various scenarios, including shops, residences, hotels, parking areas, and other relevant settings, where early carbon monoxide detection is crucial for ensuring safety. The smoke detector alerts for low voltage, tampering, and maze dirty issues, increasing its dependability. The Figaro sensor ensures precise detection. Powered by a durable lithium battery, it includes a test and self-check function for periodic checks. The detector also offers silence and reset modes for user control.

Hikvision India

<https://www.hikvisionindia.com>

## MISCELLANEOUS

### RTL design studio with AI

Cadence Design Systems Inc. has launched the Joules register transfer level (RTL) Design Studio to accelerate the RTL design and implementation process.



The tool empowers front-end designers by providing actionable

insights and debugging capabilities through a unified cockpit. Users can achieve fully optimised RTL designs before the implementation handoff by leveraging generative artificial


intelligence (AI) for RTL design exploration for big data analytics. The RTL Design Studio enables designers to obtain quick and accurate physical estimates, resulting in up to 5x increased productivity and up to 25% improvement in the RTL's quality of results (QoR). The tool integrates with a lint checker for early error detection, streamlining the design process. The unified cockpit provides RTL designers with feedback, violation analysis, and cross-probing between RTL, schematic, and layout.

Cadence Design Systems Inc

[https://www.cadence.com/en\\_US](https://www.cadence.com/en_US)

### Next-generation GH200 Grace Hopper superchip platform

NVIDIA has announced the next-generation NVIDIA GH200 Grace Hopper platform, powered by the new Grace Hopper superchip with the world's first HBM3e processor. The platform is built for the emerg-



ing demands of accelerated computing and generative artificial intelligence (AI). The dual setup provides a staggering 3.5x more memory capacity and triple the bandwidth compared to its predecessor. This configuration encompasses a server with 144 Arm Neoverse cores, eight petaflops of AI processing prowess, and a generous 282GB state-of-the-art HBM3e memory. Using NVIDIA NVLink, it links multiple superchips for efficient generative AI model processing. With the HBM3e memory clocking in at a speed 50% greater than its HBM3 counterpart, the platform achieves an astounding combined bandwidth of 10TB/sec. Consequently, this platform can operate models that are 3.5 times larger than before, coupled with a memory bandwidth that's thrice as fast, enhancing overall performance.

NVIDIA

<https://www.nvidia.com/en-in>