

Gluon has 8 TOPS that give higher utilisation (higher performance per TOPS), resulting in higher performance. Gluon further supports PCIe and LPDDR4 interfaces. As a coprocessor targeted at the edge segment, where power is often a constraint, Gluon is aimed at vision workloads, such as classification and detection. Segments where these capabilities are applied include surveillance, industrial, retail, and smart cities.

AlphaICs
www.alphaics.ai

BOARDS & MODULES

Power supplies for LED lighting

The LCM4000HV series of configurable power supplies uses a new power system that features hot swap functionality and simplifies installation, maintenance, and scalability of high-volume LED lighting projects, such as horticultural and commercial lighting. Rated for up to 4000W and operating with efficiencies of up to 95%, the LCM4000HV single-phase AC-DC high-voltage power modules, combined with the new LCM12K 19" 1U rack mount shelf, create a centralised current source for medium- to large-scale LED lighting installations. The modules provide a flicker-free current source from 0 to 16A at an output voltage between 100 and 300V DC. Input voltage options are 187 to 364V AC and 311 to 528V AC.

Advanced Energy
www.advancedenergy.com

High-speed digitiser cards

Two new PCIe digitiser cards, M5i.3330-x16 and the M5i.3337-x16, bring next generation performance to PC based instrumentation. Using 16-lane, Gen 3 PCIe technology, the cards are capable of streaming acquired data over the bus at a staggering 12.8GB/s - nearly twice as fast as any other PCIe digitiser currently available. The M5i.3330-x16 is a single-channel card

that can sample at rates up to 6.4GS/s while the M5i.3337-x16 is a dual-channel card that offers synchronous 3.2GS/s sampling on both channels, or the full 6.4GS/s on a single channel. Designed to handle a wide variety of signals, the cards feature fully functional front-end electronics with over 2GHz bandwidth, programmable full-scale ranges from $\pm 200\text{mV}$ to $\pm 2.5\text{V}$, and variable offset.

Spectrum Instrumentation
www.spectrum-instrumentation.com

DC-DC converters

The introduction of three new parts with single outputs of 24V (21.6-26.4V), 48V (43.2-52.8V), and 54V (48.6-59.4V) that retain the wide 8:1 input range of the company's PKE8000A series suit implementation for a wide range of industrial, transportation, RFP, and IT applications. Encapsulation of these power-dense DC-DC converters provides mechanical protection and reliable operation in environments with high shock and vibration levels or with high dust/humidity. An output power of 40W is available at high ambient temperatures with convection cooling, enabled by innovative design that maintains high conversion efficiency across the load and input voltage range. Maximum case operating temperature is 115°C with derating.

Flex Power Modules
www.flexpowermodules.com

Pulse motion controllers

The AMP-104C and AMP-304C pulse motion controller series, based on the PCI Express interface, provide high performance and exceptional accuracy. These controllers are engineered specifically to satisfy motion control equipment requirements in numerous high-growth electronics manufacturing fields, including the semiconductor, AOI, and LED industries. The AMP-104C is an entry-level controller that enables reliable and accurate execu-

tion of basic point-to-point motion. The AMP-304C offers incredible speed and precision while coming with the DIN-304C dedicated terminal board to help simplify cable distribution. Both AMP models feature a two-in-one design that combines motion control and I/O functionality.

ADLINK Technology
www.adlinktech.com

Server-on-module families

Three new server-on-module families have been launched that come in size E and size D for accelerating the next generation of real-time microserver workloads in rugged environments and extended temperature ranges. Up to 20 cores, up to 1TB RAM, double throughput per PCIe lanes to Gen 4 speed are included, as well as up to 100GbE connectivity and TCC/TSN support. Target applications range from industrial workload consolidation servers for automation, robotics, and medical backend imaging to outdoor servers for utilities and critical infrastructures—such as smart grids for oil, gas, and electricity as well as rail and communication networks—and include vision enabled applications, such as autonomous vehicles and video infrastructures for safety and security.

congatec
www.congatec.com

AC-DC power supplies

The TPI 300 (industrial grade) and TPP 300 (medical grade) series are a set of encapsulated AC-DC power supplies coming as open-frame and encased versions. They feature a reinforced double I/O isolation (3000V AC) system according to latest medical or industrial safety standards, respectively. With focus on the medical market, the TPP series also has a low leakage current of $< 100\mu\text{A}$, which makes the units suitable for body floating applications. An efficiency of up to

