

93% allows a high power-density. The operating temperature range is -40°C to +85°C, with derating above 50°C. The TPI 300 and TPP 300 are ideal for industrial and medical devices and for demanding safety and space-critical applications.

Traco Power
www.tracopower.com

Product development solution

The nRF21540 development bundle (DB) design tools for verification and testing of applications that require range extension or link budget improvements comprise the nRF21540 Development Kit (DK) and the nRF21540 Evaluation Kit (EK). The nRF21540 DK is ideal for application performance testing of designs. It incorporates the nRF21540 RF FEM and has two chip antennas and ports for antenna diversity and additional SWF connectors for making direct RF measurements. The nRF21540 EK is a shield incorporating the nRF21540 RF FEM and can be used for easy radio testing and development.

Nordic Semiconductor
www.nordicsemi.com

Raspberry Pi based industrial computer

The new and compact Factor 201 Raspberry Pi-powered computing device is intended for use as an industrial gateway, automation controller, or edge computer. In addition to the Raspberry Pi CM4, the system features an operating temperature range of -20 to +60°C, options for DIN rail or wall mounting, and 12-24V power input. The device can also be powered via an Ethernet cord, utilising PoE power delivery, enabling single cable installation to provide both network access and power to the device. Multiple memory and storage options allow users to match the device to the unique demands of their project.

OnLogic
www.onlogic.com

T&M SOLUTIONS

Versatile LCR meter series

These LCR meters measure AC components of 4Hz to 10MHz for all practical applications. Part of the R&S LCX family, the LCR meter series serves



all established impedance measurements plus specialised measurements for selected component types. It provides the high accuracy required in R&D and the high speed needed in production test and quality assurance. It is suitable not only for most devices operating at conventional 50 or 60Hz domestic power frequencies, or 400Hz for aircraft, but also for everything from low-frequency seismic sensors to high-power communication circuits operating at several megahertz.

Rohde & Schwarz
www.rohde-schwarz.com

Oscilloscope for optical signals

The new 25G clock recovery range expansion option MP2110A-059 upgrades the BERTWave MP2110A sampling oscilloscope clock recovery rate required



for testing optical signals. It facilitates optical-waveform tests of fibre channel compliant 64GFC PAM4 optical modules in a clock-signal-free test environment. The upgrade helps assure the quality of 64GFC PAM4 optical modules while simplifying the production line configuration to cut costs. The all-in-one MP2110A BERTWave combines a bit-error-rate tester with a sampling oscilloscope for evaluating communications waveforms.

Anritsu Corporation
www.anritsu.com

PCI Express 6.0 test solution

The PCI Express 6.0 is an important and scalable base transmitter test solution for data-intensive markets, such as data centres, artificial intelligence/machine learning, and high-performance computing. To meet ever grow-

ing performance demands, PCIe 6.0 standard transitions to PAM4 signalling and new innovative error-correcting



techniques. The test solution includes PCIe 6.0 measurement-specific software, enhanced PAM4 DSP capabilities, and noise compensation on the oscilloscope for increased accuracy of results. It is further enhanced by industry-leading analysis tools for SNDR and uncorrelated jitter measurements, which are both mandated requirements for the PCIe 6.0 standard.

Tektronix
www.tektronix.com

100Gb/s PAM4 Ethernet test platform

The addition of a new 100GbE Layer-1 adaptor in the SierraNet M648 test platform enhances the device's ability for high-speed storage and communica-



tions while also supporting the examination and modification of Ethernet and fibre channel links that utilise both PAM4 and legacy Non-Return to Zero technologies. By adding the new SierraNet 100GbE Layer-1 adaptor, the SierraNet M648 can now capture and analyse 100GbE single lane auto-negotiation and link training.

Teledyne LeCroy
www.teledynelcroy.com

Semiconductor wafer probing system

The TESLA300 high-power semiconductor probing system has been designed specifically for IGBT and power MOSFET device measurements. The TESLA300 provides accurate data at



up to 10,000V and up to 600A current on 300mm wafers. Integrating new anti-arcing and wafer automation capabilities, the TESLA300 enables high-throughput, unattended testing over a wide thermal range to speed development and lower production cost of power devices.

FormFactor
www.formfactor.com