

SOFTWARE


Single licence for T&M software bundle

A test workflow bundle has been launched that helps engineers automate test systems through a single software licence. This subscription based bundle provides access to popular test and measurement software, including LabVIEW, TestStand, FlexLogger and DIAdem, enabling engineers working on research validation and production test applications to gain actionable insights, improve test system development, deliver more value from test data, and get products to market faster. With the ability to scale up or down as needed, users have additional control over project costs.

NI
www.ni.com

Support for 64-bit RISC-V solutions

The newly introduced support for 64-bit RISC-V cores is a complete C/C++ compiler and debugger toolchain.



It has everything integrated in one single IDE, including integrated code analysis tools, ensuring code quality. It is beneficial for embedded developers to ensure their application fits the required needs and optimise the utilisation of on-board memory. In addition, symmetric multicore processing is now supported, enabling high-performance debugging of multicore RISC-V devices.

IAR Systems
www.iar.com

Monitoring software

The LIN monitoring software PLIN-View Pro version 3 helps PC interfaces with LIN connection (PCAN-USB Pro, PCAN-



USB Pro FD, PLIN-USB) to script code implementations for different LIN elements in the software. Scripting is done with the programming language Microsoft C#. The data of publisher frames from the Transmit and Publish lists can be modified as well as entries of schedule tables. For different events for these elements, a C# script can be specified in each case. The new output gives the user various feedback options about loading processes of projects or LDF files, and an additional output option for C# scripts.

PEAK System
www.peak-system.com

Software development kit

With the new version 5.70, the OPC UA C++ software development kit (SDK) comes with more enhanced options. With the help of reverse con-



nect, users can now easily establish a secure OPC UA connection with OPC UA clients across the firewall using their product's OPC UA server without opening internal binding ports. Use cases for reverse connect include company-wide, cross-domain connectivity, industrial IoT, and Industry 4.0 applications, and secure field-to-cloud OPC UA data connections. The OPC UA C++ SDK is available for Windows, Linux, and VxWorks.

Softing
www.softing.com

CHEMICALS & ADHESIVES

Liquid flip-chip flux

A new liquid flux has been developed that meets process needs for



low-temperature flip-chip applications. WS-3910 is a water-soluble, halogen-free flip-chip flux that is designed for low-temperature (150°C) bismuth-tin applications. WS-3910 is chemically designed to exhibit minimal evaporation after application. Its composition also eliminates compatibility underfills

by having a completely water-cleanable residue.

Indium Corporation
www.indium.com

ENTERPRISE CLASS

Data storage optimising solution

The auto-tiering function for the EonStor CS optimises read/write performances and utilises storage capacity for mass data analytics, such



as in large-scale, high-performance computing (HPC). Auto-tiering utilises the high-performance of SSDs and the massive capacity of HDDs. The system automatically allocates the processing 'hot data' onto high-performance SSDs to meet the mass data read/write requirements of HPC analytics. Once the data have been finalised, they are identified as 'cold data' and moved to HDDs with PB-level capacity for archiving purposes.

Infotrend
www.infotrend.com

5G-ready embedded computing system

The ASB200-953 is a compact SBC that is powered by 11th Gen Intel Core i7-1185G7E, i5-1145G7E, and i3-1115G4E processors (formerly Tiger Lake)

with a 15W TDP threshold. Aimed at smart applications in warehouse logistics management, factory automation, and



the automotive industry, the fanless ASB200-953 features high performance with low power consumption. With a black colour chassis, it supports up to 64GB in two SO-DIMM slots and 12V ~ 24V wide-range DC power input. The panel is equipped with digital I/O, power button, HDD LED, DC-in terminal block, and two antenna holes that can be used with the optional Wi-Fi accessory kit

IBASE Technology
www.ibase.com.tw