

perature range of -40°C to +65°C. The modules offer continuous short-circuit protection and pack high power density of 4.73W/cm³ in compact SIP-8 metal packages. The

series is suitable for a wide variety of operations that include application in communication equipment, instrumentation, and industrial electronics.

Traco Power

<http://www.tracopower.com>

Wireless Raspberry Pi Pico

Raspberry Pi has added wireless connectivity to its Pi Pico, the company's

smallest development board for IoT applications. The Raspberry Pi Pico W features an RP2040 microcontroller powered by 133MHz Arm Cortex-M0+ CPU cores. The newer Pico W also features an Infineon CYW43439 chip, which enables the wireless connectivity. The CYW43439 chip supports both Bluetooth Classic and Bluetooth Low-Energy along with the Wi-Fi 2.4GHz 802.11n. The board only comes with the Wi-Fi connectivity. The company is expected to add the Bluetooth connectivity through a firmware update in the near future. Like the original Pico, the newer model has 26 multi-function GPIO pins, an accurate clock, and timer on-chip and an on-board temperature sensor.

Raspberry Pi Foundation

<https://www.raspberrypi.org>

Low-power GNSS module

u-Blox has released SAM-M10Q GNSS, a low-power Global Navigation Satellite System (GNSS) with a built-in

antenna. The SAM-M10Q GNSS antenna module offers a best-in-class low-power positioning solution. The wide band antenna along with the SAW filter and low-noise amplifier (LNA) architecture offers out-of-band jamming immunity. The M10Q can offer superior position availability with concurrent reception of all four GNSS constellations, in-

cluding GPS, GLONASS, Galileo, and BeiDou. Typical applications include industrial tracking and telematics, automation and monitoring, and small UAVs.

u-Blox

www.u-blox.com

Single-board computer

IB956 from IBASE Technology Inc. is a high-performance single-board computer in a 8.9cm (3.5-inch) form



factor. Powered by an 11th Gen Intel Core processor, the

module can support up to four displays and is suitable for both fan and fan-less systems operating 24/7. The compact module can fit up to 32GB of DDR4 memory and features multiple I/O ports, such as Gigabit LAN ports, USB 3.1, USB 2.0, and SATA III, to meet the data and transmission requirements of a multitude of IoT applications. The module can run at wide operating voltages from 12V DC to 24V DC and can work with both Windows 10 and Linux Ubuntu operating systems.

IBASE

www.ibase.com.tw

Module driving AI at edge

Adlink's new AIOT SMARC 2.1 module is capable of driving AI at the edge. The AIOT SMARC module is powered by MediaTek's 8-core MT8395 CPU, which




features four power cores of Arm Cortex-A78 and four cores of Arm Cortex-A55. It is capable of handling up to 8GB of LPDDR4 RAM. The module has one onboard UFS, up to 256GBs, and features 3x MIPI CSI interfaces. It also features an integrated AI processor unit for on-device AI processing, such as deep learning, neural network acceleration, and computer vision. The module can support up to three MIPI camera inputs and extended IO connectivity.

ADLINK

<https://www.adlinktech.com>

Servers on modules

Congatec has introduced five new modules to its Xeon D-2700 processor based server-on-module portfolio. The modules will satisfy the industry demands for edge server performance



in a small form factor.

The rugged and outdoor capable modules come in a compact 160 × 160

COM-HPC Server Size D performance class. The modules feature processors with up to 20 cores, making them suitable for tasks such as hosting multiple real-time applications simultaneously. The modules provide double throughput per PCIe lane to Gen 4 speeds, as well as up to 100GbE connectivity and TCC/TSN support. Target applications of the new Intel Xeon D-2700 processor based COM-HPC modules are deeply embedded, space-constrained edge server deployments with high data throughput but less memory-intensive workloads.

Congatec

<https://www.congatec.com/en>

ENTERPRISE CLASS

Waterproof asset tracker

The AS500 LTE-M/NB-IoT is a waterproof asset tracker with a long standby from ATrack Technology Inc. The asset tracker is suitable for both indoor and outdoor unpowered asset tracking applications and can operate for up to ten years on a single charge. It utilises Wi-Fi and Bluetooth for asset tracking. The module can help business owners quickly realise cloud management and play a key role in driving customers into 'Connecting the Future.'

ATrack Technology Inc.

<https://www.atrack.com.tw/en>

Conveyor belt lidar scanner

Contour2D from Pepperl + Fuchs can ensure that packages on a conveyor belt are distributed evenly to down-



stream stations. Contour2D sensor system employs a single lidar sensor with a combina-