

R&S MXO 4 Series, The Next-Generation Oscilloscopes for Accelerated Insight

Rohde & Schwarz is adding a completely new series to its oscilloscope portfolio that delivers a number of industry firsts. The new R&S MXO 4 series oscilloscopes feature the world's fastest real-time update rate of over 4.5 million acquisitions per second. Development engineers can now see more signal detail and frequent events than with any other oscilloscope. The 12-bit ADC in the R&S MXO 4 series has 16 times the resolution of traditional 8-bit oscilloscopes at all sample rates without any tradeoffs for more precise measurements. A standard acquisition memory of 400 Mpts on all four channels gives the instrument up to 100 times the standard memory of comparable instruments.

Rohde & Schwarz presents the new R&S MXO 4 series that comes in four-channel models with bandwidths of 200 MHz, 350 MHz, 500 MHz, 1 GHz, and 1.5 GHz. They have many unparalleled functions and excel in both performance and value.

Instant view of signal details

R&S MXO 4 series oscilloscopes boast the world's fastest update rate of 4.5 M acquisitions per second, revealing more signal activity than any other available oscilloscope. Development teams can quickly see and isolate infrequent events, get a better understanding of physical layer signals, and test faster. This is unparalleled in the industry.

Lower measurement noise and the highest available vertical resolution

The R&S MXO 4 series incorporates a 12-bit ADC that operates across all the instrument sample rates with an 18-bit vertical resolution architecture for greater resolution precision than any other oscilloscope. The R&S MXO 4 series also has the lowest noise and largest offset range ($\pm 5V$ with a 500uV/div scaling) in its class. Users can see DC and other signals with more precision than with any other oscilloscope on the market.

Deepest standard memory

In addition to bandwidth and sample rate, memory depth is an important factor and determines whether an oscilloscope can handle a large range of troubleshooting tasks. More acquisition memory enables oscilloscopes to capture more time and retain rated bandwidth information for shorter time base settings. With a simultaneous standard acquisition memory of 400 Mpts on all four channels, the R&S MXO 4 series has up to 100 times the standard memory of its primary competition. The additional memory also provides extra measurement capability when needed.



High-precision digital trigger

Once only available in higher-performance oscilloscopes with higher price points, the digital trigger comes standard with all R&S MXO 4 series oscilloscopes. The trigger sensitivity of 1/10 000 division can isolate difficult-to-find small physical layer anomalies in the presence of large signals. No competitive oscilloscope has this degree of trigger sensitivity for isolating small signals. The digital trigger complements the 18-bit vertical architecture, allowing users to fully utilize the precision of the R&S MXO 4 series.

Superior RF measurement capability

Many development engineers need to debug products and test in both the time and frequency domains. In addition to time domain measurements, R&S MXO 4 series oscilloscopes have superior RF spectrum measurement capabilities. They are the first oscilloscopes to perform 45 000 FFTs (Fast Fourier Transforms) per second, while comparable oscilloscopes deliver fewer than 10 FFTs per second. This base feature enables engineers to view more RF signals than with any other oscilloscope in its class.

Enhanced user experience

This series incorporates a 13.3" full-HD capacitive touchscreen and an intuitive user interface. The instrument's small footprint, audible noise of less than a whisper, VESA mounting, and rackmount kit for installation in integrated environments make R&S MXO 4 oscilloscopes ideal for any engineering workspace.

For more information, contact us :

Mr. Srinivasa Rao Appalla,
srinivasa.appalla@rohde-schwarz.com
 or sales.rsindia@rohde-schwarz.com