

magnetic shielding to prevent interference with nearby components

Vishay Intertechnology

<https://www.vishay.com>

Wi-Fi chipset for IoT

UBI206 Wi-Fi chipset from Ubilite enables truly ultra-low-power wireless solutions. Based on the UBI206 SoC, it is a highly integrated single



device that enables a vast number of IoT products

with minimal number of external components. It includes a switchless 802.11b/g/n radio, baseband processor, medium access controller (MAC), power management unit (PMU), memories, and a network application processor that runs the Wi-Fi link-layer protocols, TCP/IP stack, and IoT applications. The UBI206 is optimised for ultra-low-power IoT markets, including wearables, trackers, beacons, healthcare, smart home, industrial systems monitoring and control, audio, etc.

Ubilite

<https://www.ubilite.com>

Air temperature and humidity sensor

SenseCAP's LoRaWAN EU868MHz is a wireless air temperature and humidity sensor that provides ultra-wide distance data transmission. The highly



integrated design features 2-in-1 sensor, a custom battery, and an industry-grade

enclosure optimised for outdoor use cases that need reliable data collection for years. With a high-precision measurement chip, this sensor features stability and reliability, making it widely applicable in industrial environmental sensing scenarios. This device incorporates a built-in long range transmitter based on SX1276 for long-range transmission. To minimise


the power consumption, the device wakes up, transmits the collected temperature and humidity data to the gateway, and then goes back to sleep. The 2-in-1 sensor can be used in a wide variety of applications, including smart agriculture, smart building, and environmental monitoring.

Seedstudio

<https://www.seedstudio.com>

Offline HV flyback regulators

RAA223181 from Renesas Electronics is a 900V offline flyback regulator optimised for high-reliability applica-



tions. It operates in discontinuous-conduction mode (DCM) with constant switching

frequency at full load. The device is inherently stable with an easy feedback loop design while switching at constant frequency without interfering with the communication of the smart meter. The flyback regulator comes with short-circuit protection, overload protection, input undervoltage lockout, over-temperature protection (OTP), etc. It is suitable for a wide variety of applications, including smart meters, power supplies, large appliances, and industrial control.

Renesas Electronics

<https://www.renesas.com>

BOARDS AND MODULES

1500W power supply

Cosel has added a new 1500W power supply to its PJMA series that works over a wide input range from 85V AC



to 264V AC. The device has a low power consumption at no load and is suitable for medical body

floating (BF) applications. It complies with medical isolation grade 2MOPP (In/Out) and 1MOPP (Out/FG) safety requirements. The power supply has been optimised to offer a good price/

performance ratio and offers a typical efficiency of up to 88%. The PJMA series of power supplies offers multiple safety features, including an inrush current limiting circuitry, overcurrent and overvoltage protection as well as thermal protection.

Cosel

<https://coselusa.com>

130W AC/DC power supply

RECOM Power has added a new 130W AC/DC power supply to its RAC-M130E-K series. It comes in a compact form factor of 5cm × 10cm and



is suitable for cost-sensitive applications requiring high performance.

The power supply has a high efficiency of around 90% and low no-load loss of less than 200mW at 230V. The module can provide a continuous output power peak of 130W in harsh environmental conditions, making it suitable for use in industries, test and measurement, IT, and household applications. It comes with a high level of safety certification and can work with an input voltage from 85V to 264V AC and provide tightly regulated single outputs, including 12V, 15V, 24V, 36V, and 48V DC.

Recom Power

www.recom-power.com

Dual-band GNSS timing module

The NEO-F10T from u-blox is a compact dual-band timing module. The new receiver can provide the security



and performance benefits of dual-band technology and offer nanosecond-level timing

accuracy. Compared to its predecessor NEO-M8T module, the NEO-F10T offers dual-band timing technology, which mitigates ionospheric errors and greatly reduces timing error