

without the need of an external GNSS correction service. The module has a single RF input for all the GNSS bands and dual SAW filters. The low-power device works on an input of 2.7V to 3.6V, drawing just 19mA @ 3.0V, during continuous operation. NEO-F10T is designed to meet the timing synchronisation requirements in 5G small cells and private networks on a global scale. The device offers advanced anti-jamming and anti-spoofing algorithms to protect it from cyber-attacks.

u-blox

<https://www.u-blox.com>

Compact DC-DC bus converter

BMR320 from Flex Power is an 8:1 non-isolated, unregulated, DC-DC intermediate bus converter that



operates over a 40V to 60V DC input range. The module comes in a compact pack-

age measuring just 27mm × 18mm × 6.4mm with an efficiency of up to 97.7%. A non-isolated DC/DC bus converter can increase efficiency and density at a lower cost. The flat design of the module allows easy integration of the heatsink, thus making the module suitable for top-side cooling to a heatsink with airflow or for liquid cooling via a thermal block. BMR320 is suitable for applications where power density, efficiency, and low cost are critical factors, including use in datacom, cloud computing, and AI.

Flex Power

<https://flexpowermodules.com>

SOFTWARE & TOOLS

IoT sensor kit

XENSIV connected sensor kit (CSK) from Infineon is an IoT sensor platform. The CSK allows users to create rapid prototypes and develop customised IoT solutions with lower resources. The sensor kit enables new service offerings and peripheral services. It also provides secure and reli-

able connectivity to the most popular cloud services like AWS IoT Core. The kit utilises Infineon's products and offers ready-to-use sensor scenarios and quick data visualisation packed



in a 10-minute IoT experience. It combines both software and hardware solutions that can help reduce time-


to-market. The CSK can be used to develop IoT products such as battery-powered smart home applications and GPS tracking applications. The board is compatible with Adafruit form factor. The CSK also provides secured and reliable connectivity to the most popular cloud services like AWS IoT Core. It can be used for publishing, configuring, and subscribing messages to and from cloud platforms.

Infineon Technologies

<https://www.infineon.com>

Phone as a key for cars

Alps Alpine and Broadcom have jointly-developed an automotive phone as a key (PaaK) system based on Bluetooth Low Energy that can enable



users to lock and unlock a vehicle without a physical key. The system employs a Blue-

tooth position measurement technology and a smartphone with Bluetooth and Wi-Fi combo chip that supports high-accuracy distance measurement. The new technology can change how we unlock and get into a car. This will enable users to open and unlock their car using their phone, making it more convenient for the user.


Alps Alpine

TEST & MEASUREMENT

Multi-spectral sensor

ams OSRAM's AS7343L is a multi-spectral sensor that can be optimised for reflective, transmissive, and emissive measurements. This 13-channel

sensor is designed for spectral identification of lateral flow particle markers. The 13 channels cover a spectral range



of 380nm to 1000nm. The AS7343L can be used for a wide variety of

applications, including lateral flow test applications, fluid or reagent analysis, colour matching, and spectral identification in the visible range. The device offers one of the highest sensitivity vs channel-count of the multi-purpose point of care diagnostics product family. It features a highly versatile sensor that can enable new laboratory applications

ams OSRAM

<https://ams.com>

Plug-and-play margin tester

TMT4 margin tester from Tektronix is a plug-and-play PCI Express testing equipment with an easy-to-use interface built on the Intel Stratix 10 FPGA with PCIe. It employs a new approach



to simplify and speed up design and validation of PCIe Gen 3 and Gen 4

motherboards, add-in cards, and system designs. Unlike most testers, the TMT4 can enable even inexperienced engineers to evaluate the health of transmitter and receiver, thus reducing time to market and cost of ownership. The platform supports the majority of common PCIe form factors, including CEM, M.2, U.2, and U.3, with testing capabilities of up to 16 lanes across PCIe presets 0-9, using a single standard connector.

Tektronix

<https://www.tek.com/en>

Diode power sensor

R&S NRP90S(N) from Rohde & Schwarz is a diode power sensor for power measurements up to 90GHz. It offers a frequency range of 50MHz to 90GHz with a dynamic range from