



**MADE IN
SOUTH KOREA**



MAIN FEATURES WITH SPECIFICATIONS

Fast printing of texts and images

To speed up customer transactions without sacrificing performance, the SRP-350III prints texts and graphics at a consistent speed of 260mm per second which is amazingly 30% faster than the industry leading the SRP-350. The SRP-350III guarantees smooth and speedy printing without any interruptions during printing.

High-speed USB 2.0 on board standard

The SRP-350III has USB 2.0 interface on the main board as a standard and has an additional interface slot for an optional Serial, Parallel or Ethernet interface card. New POS systems are starting to be equipped with USB 2.0 but most thermal printers in the market only support version 1.1 of USB whose full speed is 12 Mbps. BIXOLON SRP-350III now supports the new USB 2.0 standard with a High Speed of 480 Mbps. The USB 2.0 interface of the SRP-350III has downward compatibility for USB1.1.



USB 2.0 on board


Long lasting auto-cutter



The new auto cutter of the SRP-350III has long lifespan up to 1.8 million cuts. It has specially designed components such as gears, cutting blade and covers to guarantee its lifetime. In addition, it also has a manual wheel conveniently positioned for easy clearing of the paper jam.

Customer oriented software tools

The new customer oriented utilities enable the users to directly access logo download (NV Image Tool), code page selection (Virtual Memory Switch Manager), firmware download and the other printer settings more easily and with No Hardware setting changes.



Two different models

- SRP-350III (without BLE) • SRP-350 PlusIII (with BLE)

3" Thermal Printer

SRP-350III

Dual-Interface and
High-Performance

With improved functions and specifications, the SRP-350III is a leap forward in technology representing BIXOLON's commitment to supply the best and the right product for our customers and our partners.

PRINT

- PRINTING METHOD : Direct thermal
- PRINTING SPEED : 260mm/sec (SRP-350 PlusIII: 300mm/sec)
- RESOLUTION : 180 dpi (7 dot/mm) / 203 dpi (SRP-352III)
- CHARACTER SIZE : Font A: 12 X 24 / Font B: 9 X 24
Korean: 24 X 24 / Chinese: 24 X 24
- CHARACTERS PER LINE
SRP-350III - Font A: 42 / Font B: 56, Korean: 21 / Chinese: 21
SRP-350plusIII - Font A: 48 / Font B: 64, Korean: 24 / Chinese: 24
- CHARACTER SET : Alphanumeric Character: 95
Extended Character: 128 X 34 pages
International Character: 32
- BARCODES
1D : EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda Bar, UPC-A, UPC-E
2D : PDF417, QR Code

PAPER

- WIDTH : 80mm
- PAPER ROLL DIAMETER : Max Ø 83mm
- SUPPLY METHOD : Easy Paper Loading

RELIABILITY

- PRINTER UNIT : 70,000,000 Lines
- TPH : 150 Km
- AUTO CUTTER : 1,800,000 cuts

INTERFACE : USB 2.0 on board, RS-232C, IEEE1284, Ethernet, Bluetooth

RECEIVE BUFFER : 4 Kbytes. (64 Mbit RAM)

NV IMAGE MEMORY : 256 Kbytes (Mono / Color)

USER DEFINE BUFFER : 12 Kbytes

EMULATION : ESC / POS ; BXL/POS

DRIVER : Win 7-10 / VISTA, OPOS, JPOS

SENSOR : Paper Near End Sensor, Paper End Sensor, Cover Open Sensor

DRAWER PORT : 2 Ports

POWER SUPPLY (SMPS) : AC 100-240V / DC 24V, 2.5A

DIMENSIONS : 145 X 195 X 146 (W X L X H mm)

OPERATING TEMPERATURE : 0 ~ 45°C

OPTION

- WALL MOUNT (RWM-350)
- SPLASH COVER (RSC-350)

Authorized Bixolon Distributor- Maxim Peripherals Pvt.. Ltd. :
106, Pradhan Bldg., Aarey Road, Near Subway, Goregaon (East), Mumbai 400 063, India
Email: support@maximpp.com Cell:+91- 9372573685

BIXOLON
SAMSUNG mini printers