

and drones in consumer, enterprise, defence, industrial, and logistics sectors. For robotics and autonomous robot solution providers, the module provides the capability to build powerful robots for use in harsh industrial conditions and in temperatures that range from -30° to +85°C. It provides enhancements for computer vision applications with reduced latencies for real-time image processing decisions, freeing up capacity for other critical AI applications.

ADLINK Technology
www.adlink.tech.com

AC-DC power supply

The Excelsys Xsolo XB1000 series is an ultra-compact single-output AC-DC power supply for Type BF medical



applications featuring market-leading 92% efficiency and user-defined output setpoint voltages. XB1000 power

supplies have the safety approvals required to simplify and speed the development and certification of a wide range of applications, including acoustically sensitive laboratory and medical systems requiring Type B (body) and Type BF (body floating) ratings. The XB1000 comes with maximum output power up to 1000W with output voltages of 24 or 48V. Meeting the stringent creepage and clearance requirements for medical applications, the XB1000 provides 4kVAC isolation, 2MOPP, as well as the low leakage currents required for body floating applications.

Advanced Energy
www.advancedenergy.com

AC-DC power supply

The new TPP 40E and TPP 65E families of miniature encapsulated AC-DC



power supplies with safety approvals for both medical and industrial applications consist of 6 models within each

wattage family offering single outputs of 5/12/15/24/36/48V with up to 94% efficiency. The small footprint with PCB or chassis-mount versions makes these an attractive solution for a wide range of requirements. The operating temperature range is -40°C to +80°C with derating above 60°C. The EMC characteristic is dedicated for applications in industrial and medical fields. High reliability is provided by use of high-quality components and excellent thermal management, making the TPP 40E and TPP 65E ideal for medical devices and for demanding safety and space-critical applications.

TRACO POWER
www.tracopower.com

Rugged computers

The Karbon 800 series of rugged computers is designed to leverage the advanced features and capabilities of Intel's latest CPUs. It includes



PCIe Gen 4 expansion for the latest GPUs, new

I/O options like 10GbE and M12 LAN, and new configurations including a high-capacity RAID array option. The series has been engineered for machine learning, artificial intelligence, advanced manufacturing, automation, and other Industry 4.0 and industrial IoT applications that require powerful computing in commercial and industrial environments. Available in four models, each can be configured with up to a 16-core, Intel Core i9 processor and 64GB DDR4 ECC or non-ECC memory.

OnLogic
www.onlogic.com

T&M SOLUTIONS

Radar scene emulator

Keysight's radar scene emulator enables automakers to lab-test complex, real-world driving scenarios, accelerating the overall speed of the test. Full-scene emulation in the lab is critical to developing the robust radar sensors

and algorithms needed to realise ADAS/autonomous driving capabilities. The full-scene emulator combines hundreds of miniature radio frequency



front ends into a scalable emulation screen representing up to 512 objects and distances as close as 1.5 metres.

Using full scene rendering that emulates near and far targets across a wide continuous field of view, it enables customers to rapidly test automotive radar sensors integrated in autonomous driving systems with highly complex multi-target scenes.

Keysight Technologies
www.keysight.com

Interposer system

The PCI Express 5.0 EDSFF interposers for analysis of enterprise and datacentre small form factor (EDSFF) E1.S, E1.L, E3.x type solid-state drives (SSDs) and devices work in combination with the Summit family of PCI Express 5.0 protocol analysers to test



product designs that utilise the PCIe 5.0, NVMe Express (NVMe), and Compute Express Link (CXL) protocol technologies.

The PCIe 5.0 EDSFF interposers allow users to debug enhanced power management and link training equalisation through correlated and time aligned physical and protocol layer views. Based on the PCIe 5.0, NVMe, and CXL specifications, the EDSFF interface can support speeds of up to 32GT/s, enabling design and test engineers to test, identify issues, and optimise EDSFF (E1.S, E1.L, E3.x) type memory systems and solid-state drive performance.

Teledyne LeCroy
www.teledynelcroy.com

SOFTWARE

Machine-learning software

The Version 3 of NanoEdge AI Studio,