



NEW PRODUCTS

MAKE IN INDIA

COMPONENTS

High-current sensor

The high-current ± 65 -amp MCx1101 current sensor designed for wideband gap applications is available in 3.3- and 5-volt versions. This accurate, wide bandwidth AMR (anisotropic magneto-resistive) based current sensor is ideal for next-generation power systems and applications. It enables power system designers to use higher speeds and smaller components of wide band-gap switches. The MCx1101 also provides an integrated over-current detection (OCD) flag to help implement the OCD required in modern power systems.

Aceinna

www.aceinna.com

Cost-effective lidar SoC

The Surya lidar system-on-a-chip (SoC) enables advanced driver assistance systems and autonomous driving. It is designed for high-performance lidar and integrates both high-speed analogue to digital converters and digital signal processing to facilitate the reliable detection of long-range targets. The SoC consumes significantly lower power as compared to current architectures and is substantially more cost-effective than current FPGA based designs.

indie Semiconductor

www.indiesemi.com

Wireless power supply chipset

The chipset is capable of providing up to 1W wireless power for compact and streamlined wearable devices,

and for industrial smart, miniaturised, and sealed solutions. The ML7661 (transmitter) and ML7660 (receiver)



eliminate the need for an external microcontroller by incorporating a control circuit required for transmission/reception, resulting in a small system size in the 1W class. This makes it ideal for wearables with a large battery capacity designed to be worn for long time frames. The adoption of the high 13.56MHz frequency band enables support for Near Field Communication.

ROHM Semiconductor

www.rohm.com

Wireless microcontroller

The new, secure RSL15 wireless microcontroller (MCU) has low power consumption. Enabled with Bluetooth Low Energy wireless connectivity, it addresses the growing demand of connected industrial applications for security without sacrificing power consumption. The RSL15 is designed with Arm TrustZone technology to establish device root of trust as well as Arm CryptoCell-312 technology to protect the authenticity, integrity, and confidentiality of code and data. It supports new capabilities provided by Bluetooth 5.2 specification, including longer range, higher data transmissions, and localisation.

onsemi

www.onsemi.com



Multichannel timing devices

The second-generation family of ClockMatrix 2 high-performance, precision, multi-channel timing devices for 400/800Gbps optical transport



and wireline network applications delivers improved performance with

phase jitter as low as 88fs-rms. The highly integrated devices provide all the functionality needed to implement an IEEE1588 clock solution with jitter attenuation capabilities resulting in ultra-low jitter clock outputs for synchronous Ethernet PHYs with data rates up to 112Gbps PAM-4, reducing design complexity and bill of materials requirements.

Renesas Electronics

www.renesas.com

Low power-loss MOSFETs

The new super-junction STPOWER MDmesh K6 series MOSFETs enhance several key parameters to minimise system-power losses. These are espe-



cially suited for lighting applications based on flyback topology, such as LED drivers, HID lamps, as well as adaptors and

power supplies for flat-panel displays. In addition, the K6 series has a reduced threshold voltage compared with the previous MDmesh K5 generation, enabling a lower driving voltage and thus reducing power losses and gaining efficiency mainly for zero-watt standby applications.

STMicroelectronics

www.st.com

Touchscreen controller

The new maXTouch touchscreen controller allows automotive designers to satisfy various and unique