

10.4V/67.4A output over a 40-60V input (80V/100ms) and can also deliver up to 950W peak for less than



one second. The BMR4920300/864 has the same input range and features an output of 12V at 66.7A, delivering 800W continuous and 1100W peak. Both models are in the industry standard eighth-brick format. Advanced thermal management techniques achieve better than 97% efficiency at half load, with high efficiency maintained at less than 10% load.

Flex Power Modules
www.flexpowermodules.com

V2X connectivity hub

Built on NXP's i.MX 8XLite, the newly developed hybrid V2X connectivity hub comes with the provision to fit in



as a rugged telematics gateway. It is designed to enable the connection between smart cities and connected mobility. Integrated with C-V2X and DSRC technologies, the hybrid V2X hub can be positioned as an on-board unit within the vehicles as well as a road-side unit to fit into external infrastructure.

iWave Systems
www.iwavesystems.com

Industrial power supply

The 700W power supply for industrial applications, the OFI700A, is optimised for conduction cooling while delivering high performance levels across a baseplate temperature range of -40 to +95°C, without the use of a fan. It operates with a wide universal input



range of 85 to 264V AC with power factor correction and is available with DC outputs of 12V, 28V (adjustable to 24V) or 48V DC. A 12V auxiliary is also provided. For safety, the OFI700A has an IN/OUT isolation of 3,000V AC and IN/FG of 2,000V AC.

Powerbox
www.prbx.com

GNSS positioning module

The NEO-M9V global navigation satellite system (GNSS) is a positioning receiver that offers both untethered dead reckoning and automotive dead reckoning. It is a perfect fit for fleet management and micro-mobility applications that require reliable meter-level positioning accuracy even in challenging GNSS signal environments such as urban canyons. NEO-M9V is based on the u-blox M9 GNSS technology platform. Its ability to track up to four GNSS constellations maximises the number of GNSS satellites within its line of sight at any given moment.

u-blox
www.u-blox.com



Medical-grade power supply

The new 700W medical-grade enclosed power supply, the TAAM700, provides 17.8W per cubic inch and a wide operating temperature range of -30 to +70°C for thermally challenged environments. Coupled with its compact size, its power density is ideal for space-constrained healthcare and industrial equipment, such as laser devices and robotics. The highly efficient and cost-effective power supply provides 625 to 700W



continuous output power with a remote on/off function, optional built-in current share (configurable to 1.26kW), and features BF rated outputs.

TT Electronics
www.ttelectronics.com

Automotive GNSS chipset module

The Teseo-VIC3DA, the latest member of the Teseo module family, supports the positioning market with state-of-



the-art GNSS chipset and modules. Teseo-VIC3DA combines ST's high-performing

automotive Teseo III GNSS IC with the automotive 6-axis MEMS inertial measurement unit and dead reckoning software to create a convenient, automotive-qualified navigation module. The Teseo-VIC3DA module operates from 3.3V, helping to simplify system integration, and has a standby mode that draws just 17µA to minimise demand on the vehicle's electrical supply.

STMicroelectronics
www.st.com

AC-DC modules

Two 5W board-mount AC-DC products, the RAC05E-K series and the RAC05E-KT series, have an input range of 90 to 264V AC (130 to 370V DC) and outputs of 4, 5, 12, 15, and 24V.



Outputs are semi-regulated but stay within ±5% over line, load, and temperature variation from -25 to +55°C. Both the -K and -KT variants also operate up to +75°C with derating. No-load power consumption is less than 100mW and



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?
Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!