

light load efficiency is high, enabling significant standby power to be drawn without exceeding ErP limits.

RECOM Power

www.recom-power.com

Battery management system

The new i-BMS battery management system (BMS) for electrified applications up to 60V is a cell chemistry agnostic, compact, integrated BMS



developed for the cost-optimised mass production of applications


up to 60V, such as 2-, and 3-wheelers, automated guided vehicles, and robotics. The i-BMS PCB board is equipped with critical components, including a pre-charge circuit, on-board current measurement, MOSFET power switches for battery disconnect, and a DC/DC power supply. Advanced algorithms ensure accurate state-of-power and state-of-health calculations.

Sensata Technologies

www.sensata.com

WiFi+BLE solution

The MiniMOD-W24 is a complete WiFi+BLE subsystem that complies with IEEE 802.11b/g/n and supports Station mode, SoftAP mode, and



SoftAP+Station mode.

Features of Bluetooth include 32-bit RISC-V single-core processor, 384kB ROM, 4MB

embedded flash, -40 to +85°C ambient temperature, and more. Features of Wi-Fi include data rate up to 150Mbps, and more. The device is suitable for smart homes, healthcare, electronics, smart agriculture, and retail.

SSTPL

www.sstpl.in

T&M SOLUTIONS

Digital oscilloscope

The SDS6000A series is available with a maximum bandwidth of 2GHz. In addition to the higher bandwidth, the device offers 5GS/s per channel. Interpolation technique ESR (enhanced

sample rate) is implemented for equivalent sample rates up to 10GS/s per channel, which significantly



improves the quality of the acquired signals.

The device has consistently been optimised to deliver a high level of signal integrity.

The newly designed input stage delivers great performance (SFDR > 45dBc, channel-to-channel isolation up to 70dB, DC amplifier accuracy $\pm 1.5\%$).

Siglent Technologies

www.siglent.com

Signal generator

The Rubidium signal generator family delivers outstanding signal purity and frequency stability, even at high output power levels across a broad frequency range of 9kHz to 43.5GHz.



Coupled with built-in, easy-to-use,

at-location frequency and power calibration capability, Rubidium offers exceptional overall utility and long-term value in a broad range of commercial and military/aerospace measurement applications. The Rubidium signal generator features built-in, on-site frequency and level calibration that is easily accessible with the touch of a button on the GUI interface, ensuring accurate frequency desired, time saving, and enhanced convenience.

Anritsu

www.anritsu.com

RF power meter

The GEMINI 5540A radio frequency (RF) power meter delivers highly accurate in-line RF power measurement in a flexible and convenient integrated



unit for applications requiring precision RF power control in semiconductor, communication, industrial, and medical

markets. Combining sensor and meter capability into a single, easy-to-use instrument, GEMINI 5540A measures at frequencies from 0.2 to 200MHz and powers from 3 to 5,000W with


2-sigma accuracy of $\pm 0.5\% + 0.5W$, enabling use of a single meter instead of multiple instruments for applications that require precise measurement and control of RF power.

Advanced Energy

www.advancedenergy.com

Radome tester

The R&S QAR50 is for testing radomes and bumpers in production. The tester's innovative design ensures



short measurement time and accurate, reproducible results with a very attractive price/performance ratio. A highly modular software

concept allows the R&S QAR50 to be adapted to individual requirements. It uses microwave imaging, which has numerous advantages compared to conventional, unfocused single-point measurements.

Rohde & Schwarz

www.rohde-schwarz.com

NAND wafer test equipment

The new T5221 is a high-throughput memory tester for NAND flash devices that can perform functional testing of chips while delivering highly accurate timing, repeatability and failure detec-



tion. With data-transfer speeds that are more than five times faster than its predecessor, the T5221 improves production efficiencies while reducing test

costs for wafer sorting, built-in self-testing (BIST), and wafer-level burn-in (WLBI). System features include two driver pins and one I/O pin for each device under test as well as a flexible algorithmic pattern generator (ALPG), a waveform generator, and various self-diagnostic functions.

Advantest

www.advantest.com

SOFTWARE

Remote monitoring software

WebLytics is a unique production monitoring, device diagnostics, and