



NEW PRODUCTS

MAKE IN INDIA

COMPONENTS

LDO regulators

ROHM's BD9xxN1 series of ultra-low dropout (LDO) regulators are capable of providing stable operation at nanoscale



output capacitance. These are specifically developed and optimised for connection to 12V power sup-


plies for a wide range of applications, such as powertrain, body, ADAS, and car infotainment systems. The regulators can handle wide range of output capacitances (as low as 1µF) and come in ultra-compact 0603/0402 size.

ROHM

<https://www.rohm.com>

Spectral sensor

ams OSRAM AS7343 is a spectral sensor capable of matching the human eye's perception of colour and light intensity. It combines 14-channel spectral analysis of visible and infrared



light (IR) with XYZ sensor technology to measure the colour and intensity of


light as seen by the human eye. Its automatic ADC reconfiguration also gives a faster multi-channel readout. The compact size of the sensor makes it easy to accommodate space-constrained applications. The AS7343 is suitable for colour analysis in applications which require frequent, accurate measurements, such as in horticulture, smoke detection, etc.

ams OSRAM

<https://ams-osram.com>

Qi 1.3 wireless charging platform

WLC1115 transmitter controller IC from Infineon is the first addition to the WLC family of controllers for inductive wireless charging. It is a Qi v1.3.2-certified MP A11 power transmitter reference solution. The IC supports a



wide input voltage (from 4.5V to 24V) along with multipath voltage- and current-based ASK demodulation. The charging platform includes a USB-PD/PPS sink, DC/DC controller, gate drivers for DC/DC, a full-bridge inverter, sensing peripherals, and configurable flash memory. The targeted applications include smartphones, smartwatches, speakers, as well as industrial or healthcare accessories.

Infineon Technologies

<https://www.infineon.com>

BLDC drivers for server fans

A89332 and A89332-1 from Allegro MicroSystems are 3-phase sensorless BLDC gate drivers. These two models



are industry's first code-free solution for server cooling fans. The

A89332 has an integrated power loss brake feature while the A89332-1 has an AC-loss feature. These drivers enable compact, high-airflow fan designs to improve thermal efficiency, reducing energy use and data centre costs.

Allegro MicroSystems

<https://www.allegromicro.com/en>

SoC for good connectivity

Dimensity 1050 system-on-chip (SoC) combines mmWave and sub-6GHz technology to provide good connectivity even in densely populated areas. The chipset is powered by an octa-core CPU, and it integrates an



Arm Cortex-A78 CPU and the Arm Mali-G610 graphics engine. It also supports True

Dual 5G SIM (5G SA + 5G SA) and Dual VoNR. The chip is capable of providing superior connectivity to the next generation of 5G smartphones, displays, gaming consoles, etc.

MediaTek

<https://www.mediatek.com>

Op-amp in DFN8 package

TSV772 is a dual operational amplifier (op-amp) with rail-to-rail inputs and outputs, 20MHz bandwidth, and a unity-gain. It offers a maximum



of 200µV as input-offset voltage and ensures accurate handling of low-ampli-

tude signals. The op-amp is capable of starting from a low input voltage of 2V and can be connected to the same rail as a low-power microcontroller to simplify the design. It offers a slew rate of 13V/µs, 7nV/√Hz input noise density, and 4kV ESD capability (HBM). The component comes in a compact DFN8 package.

ST Microelectronics

<https://www.st.com>

ESD protection devices

PESD2V8Y1BSF and PESD4V0Y1BCSF are new electrostatic discharge (ESD)