



# Achieve Your Design Goal With the AVR® DD MCU Family

## Comprehensive, Memory-Rich Feature Set Fills the Gaps in Your Design

Ideal for real-time control functions in industrial control, home appliance, automotive and Internet of Things (IoT), the AVR® DD microcontroller (MCU) builds upon the low-power performance of the AVR core with a world-class selection of Core Independent Peripherals (CIPs).

With its comprehensive feature set, including Multi-Voltage Input/Output (MVIO), the AVR DD MCU family is perfectly suited for complex applications or as a companion MCU in complex designs with multiple power domains.

Begin designing with the AVR DD MCU family to fill any gaps in your design.

### Key Features

- Internal 24 MHz oscillator
- Up to 64 KB of Flash memory and 8 KB SRAM
- Available in a wide range of package options, from 14- to 32-pins
- USART/SPI/dual-mode Two-Wire Interface (TWI)
- MVIO on Port C
- Various peripherals, including Zero-Cross Detector (ZCD), Clock Failure Detect (CFD), Event System (EVSYS) and Cyclic Redundancy Check (CRC) scan

### Contact Information

Microchip Technology India

Email: [asia.inquiry@microchip.com](mailto:asia.inquiry@microchip.com)

Phone: • Bangalore (080) 3090-4444 • New Delhi (012) 0496-3497 • Pune (020) 4121-0141



[microchip.com/EFY-AVRDD](http://microchip.com/EFY-AVRDD)



The Microchip name and logo, the Microchip logo and AVR are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks are the property of their registered owners.  
© 2022 Microchip Technology Inc. and its subsidiaries.  
All rights reserved.